Replaced by HBL10P105NM, SPIKESHIELD Wired-In Branch Panel Protection, 100KA, 3PH 347/600V, with Filter

By Hubbell Wiring Device-Kellems Catalog # HBL10W100C

SPIKESHIELD Wired-In Branch Panel Protection, 100KA, 3PH 347/600V, with Filter

Features

- Brick design for space consumption
- NEMA 4X housing and a 200kA SCCR rating

Performance

- Electrical Diagnostics Green Status LED's, Audible Alarm, Dry Contacts
- Electrical Surge Current per Phase 100kA
- Environmental Operating Temperature -40°F to 140°F (-40°C to 60°C)
- Mechanical Terminal Accommodation #10 AWG 18.0" Wire Leads

General

Catalog Number HBL10W100C

EU RoHS Indicator

Indicator(s) Type

Item Type

Material

Material - Mounting Hardware

Operating Temperature

Response Time

Series

Specifications

Nο

Green Status LED, Audible

Wired-In Branch Panel

Protection

Steel

Mounting Screws

-40 Degrees F to 149 Degrees

F (-40 C to 65 C)

Wired-In Panels

• Dimensions - 3.1"D x 9.9"W x

4.8"H

• Frequency - 50/60 Hz

• NEMA - Type 4X

Warranty - 10 year

• Weight - 4.78 lbs



UPC 783585120843

Dimensions

Display Size 100kA Peak

Electrical Ratings

Connectivity Leads Frequency Rating 60 Hz

Phase Three Phase

Voltage Rating Wye 347 VAC V • Wye 600 VAC V

Voltage Rating Description

Certifications And Compliance

Industry Standard(s) cULus UL1449-3Rd Edition

Type 2 Spd

347/600 VAC Wye

Product Assets

Catalog Page - WDK M-6 Catalog Page

Catalog Page - WDK M-22 Catalog Page

Catalogs - WDK Catalog Full 2024

Engineering Drawing - HBL10W100C AutoCAD Drawing

Installation Manuals - WIRING_PD_HBLxW100C_INSTALLINST

Literature - SpikeShield® Power Quality Surge Protective

Devices

Literature - Industrial Solutions

Sales Drawings - WDK HBL10W100C DRAWING PDF

Specifications - HBL10W100C

Specifications - HBL10W100C Specification Sheet English Specifications - HBL10W100C Specification Sheet French

Warranty - SPD Series: 320kA, 160kA, 100kA, 120kA, 80MkA &

50kA

