



Locking Devices, Twist-Lock®, Marine Grade, Male Plug, 30A 125V, 2-Pole 3-Wire Grounding, L5-30P, Screw Terminal, Yellow

By Hubbell Wiring Device-Kellems
Catalog # [HBL26CM11](#)



Twist-Lock® Marine Grade Male Insulgrip® Plug, 30A 125V AC, 2-Pole 3-Wire Grounding, NEMA L5, Screw Terminal, Corrosion resistant Nylon.

Features

- Ribbed nylon housing provides a secure grip and impact and chemical resistance
- Superior cord grip design protects terminations from excess strain
- Integral dust shield protects wiring chamber from dust or contaminants

Application

Extra Heavy Duty Industrial/Marine

General

Color	Yellow
Cord Range	0.360"-0.930" (9-24)
Environmental Conditions	Corrosion Resistant
Horsepower - Maximum	2
Item Type	30A Corrosion Resistant Insulgrip® Plug
Material	Nylon
Material - Mounting Hardware	Cord Mounted
Number Of Poles	2-Pole
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Performance	<ul style="list-style-type: none"> • Electrical - Current Interrupting - Certified for current interrupting at full rated current • Electrical - Dielectric Voltage - Withstands 2,000V minimum • Environmental - Flammability - HB or better per UL94 or CSA 22.2 No. 0.6 • Environmental - Moisture Resistance - IP20 Suitability • Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact) • Mechanical - Terminal Accommodation - #16

Electrical Ratings

Amperage Rating	30 A
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	30 A
Current Rating	30 A
Dielectric Strength	Withstands 2,000V minimum
Phase	Single Phase
Voltage Rating	125 VAC
Voltage Rating Description	125 VAC

Conductor Related

Cable Range	0.360 - 0.930 in
Cord Type	All Listed Portables
Number Of Wires	3-Wire
Wire Size	#16 AWG to #8 AWG

Certifications and Compliance

Industry Standard(s)	<ul style="list-style-type: none"> • Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498
Nema Rating	L5-30P
Standards - RoHS Compliance Status	CM

Logistics

Carton Quantity	10
-----------------	----

Product Assets

- [Catalog Page - WDK B-28 Catalog Page](#)
- [Catalog Page - WDK AA-11 Catalog Page](#)
- [Catalog Page - WDK AA-5 Catalog Page](#)
- [Catalogs - WDK Catalog Full 2023](#)
- [Engineering Drawing - HBL26CM11 AutoCAD Drawing](#)
- [Installation Manuals - WIRING_PD1651_INSTALLINST](#)
- [Literature - Hubbell Marine Full Line Catalog](#)
- [Sales Drawings - WDK_HBL26CM11_DRAWING_PDF](#)
- [Warranty - Industrial & Commercial Products](#)
- [Video - Marine Electrical Products](#)
- [Video - Insulgrip Twist-Lock and Straight Blade Devices](#)
- [Video - Twist-Lock Devices](#)

Related Products

	AWG - #8 AWG stranded copper wire only	HBL26CM10 - Locking Devices, Twist-Lock®, Marine Grade, Flush Receptacle, 30A 125V, 2-Pole 3-Wire Grounding, L5-30R, Screw Terminal, Yellow
Type	<ul style="list-style-type: none"> Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 Plugs Plugs 	<p>HBLTL2CCGR - Twist-Lock Devices, Colored Cord Clamp, Size 2, Green</p> <p>HBLTL2CCBR - Twist-Lock Devices, Colored Cord Clamp, Size 2, Brown</p> <p>HBLTL2CCBL - Twist-Lock Devices, Colored Cord Clamp, Size 2, Blue</p> <p>HBL26CM13 - Locking Devices, Twist-Lock®, Marine Grade, Female Connector Body, 30A 125V, 2-Pole 3-Wire Grounding, L5-30R, Screw Terminal, Yellow</p>
UPC	783585039084	

Dimensions

Dimensions	2.26 in x 2.26 in x 2.75 in
Display Size	Standard Sized
Height	2.75 in
Length	2.26 in
Weight	0.30 lb
Width	2.26 in



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
WDK_CA-HBL26CM11-SPEC-EN | REV 1/2024