



# Straight Blade Devices, Receptacles, Duplex, Compact Hospital Grade, 2-Pole 3-Wire Grounding, 15A 125V, 5- 15R, Brown, Single Pack

By Hubbell Wiring Device-Kellems  
Catalog # [HBL8200H](#)



Straight Blade Duplex Receptacle, Compact Hospital Grade, 2-Pole 3-Wire Grounding, 15A 125V, 5- 15R.

## Features

- Slender/compact design
- Impact-resistant finger groove face
- Triple wipe contacts

## Application

Slender/Compact Hospital Grade

## General

Color	<ul style="list-style-type: none"> <li>• Brown</li> <li>• Marron</li> </ul>
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Horsepower - Maximum	0.5
Item Type	Traditional Duplex
Material	Thermoplastic
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Performance	<ul style="list-style-type: none"> <li>• Electrical - Current Interrupting - Certified for current interrupting at full rated current</li> <li>• Electrical - Dielectric Voltage - Withstands 2,000V minimum</li> <li>• Environmental - Flammability - UL 94 V-0</li> <li>• Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact)</li> <li>• Mechanical - Product Identification - Ratings are a permanent part of the device</li> <li>• Mechanical - Terminal Accommodation - #14-#10 AWG stranded or solid copper wire only</li> </ul>

## Dimensions

Dimensions	3.28 in x 1.33 in x 1.05 in
Display Size	Slender/Compact
Height	1.05 in
Length	3.28 in
Weight	0.25 lb
Width	1.33 in

## Electrical Ratings

Amperage Rating	15 A
Connectivity	Back and Side Wired Screw Terminals
Current / Amperage Rating	15 A
Current Rating	15 A
Dielectric Strength	Withstands 2,000V minimum
Phase	Single Phase
Voltage Rating	125 V
Voltage Rating Description	125 V
Wattage	1875 W

## Conductor Related

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG

## Certifications and Compliance

Industry Standard(s)	<ul style="list-style-type: none"> <li>• CSA Certified, C22.2, No. 42 File 285</li> <li>• Fed. Spec. W-C-596</li> <li>• NEMA® WD-6 Compliant</li> <li>• UL Listed to UL498 File No. E2186</li> </ul>
----------------------	--

Nema Rating	5-15R
Standards - RoHS Compliance Status	CM

## Logistics

Carton Quantity	10
-----------------	----

## Product Assets

[Catalog Page - WDK A-9](#) [Catalog Page - WDK L-4](#) [Catalog Page - WDK L-4](#)

- Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

Catalogs - WDK Catalog Full 2023  
Engineering Drawing - HBL8200H AutoCAD Drawing  
Installation Manuals - WIRING\_PD2615\_INSTALLINST  
Literature - Duct Products Guide  
Sales Drawings - WDK\_HBL8200H\_DRAWINGS\_PDF  
Warranty - Industrial & Commercial Products

Series

Hospital Grade

Style

Finder Groove Face

Type

- Receptacle

- Receptacle

UPC

783585015828



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
WDK\_CA-HBL8200H-SPEC-EN | REV 1/2024