

Surge Protective Devices, SPIKESHIELD TVSS Duplex Receptacle with Light, 15A 125V, 5-15R, Ivory

By Hubbell Wiring Device-Kellems Catalog # HBL5260ISA

Surge Protective Devices, SPIKESHIELD TVSS Duplex Receptacle with Light, 15A 125V, 5-15R, Ivory



Application

Decorator Duplex

General

Color Ivory

Environmental Conditions Indoor Dry Unless Protected

By Additional Means

Mounting Screws

C to 60 Deg C)

Hubbell Wiring Device-

Indicator(s) Type

Item Type Surge Protection Receptacles

Material Composite

Material - Mounting Hardware

OEM Brand Name

32 Deg F to 140 Deg F (O Deg

Operating Temperature

Outlet

Straight Blade Performance

• Electrical - Protection Modes - Normal and Common Modes

Electrical - Response Time - Approximately 5 ns

• Electrical - Transient Suppression - Peak Energy (10 X 100 μ s), Peak Current $(8 \times 20 \mu s)$

Electrical - Voltage - 120V AC + 10% - 15%

• Environmental -Flammability - UL 94V-2

Environmental - Operating Temperature - 32°F to 140°F (0°C to 60°C)

Response Time

Series Specification Grade

Туре Duplex

UPC 783585060996

Dimensions

Display Size Standard

Electrical Ratings

15 A Amperage Rating

Terminal Screws Connectivity

15 A Current / Amperage Rating Current Rating 15 A Frequency Rating 60 Hz Phase Single Phase

Voltage Rating 125 V Voltage Rating Description 125 V

Certifications and Compliance

Industry Standard(s) · CSA Certified to

Specification C22.2 No. 42

• Listed to UL Standards 498

• UL Listed File E2186

Nema Rating 5-15R

Logistics

Carton Quantity 10

Product Assets

Catalog Page - Wiring N-13 Catalog page

Catalogs - Wiring Full Catalog

Engineering Drawing - HBL5260ISA AutoCAD Drawing Installation Manuals - WIRING PD1152 INSTALLINST

Literature - SpikeShield® Power Quality Surge Protective **Devices**

Literature - Residential Product Guide

Literature - Residential Catalog

Sales Drawings - WDK_HBL5260_DRAWING_PDF Warranty - Industrial & Commercial Products