

Kellems Wire Management, Deluxe Cord Grips, Straight Male, 2.312-2.437", 2 1/2" with Mesh

By Hubbell Wiring Device-Kellems
Catalog # [074011266](#)

Kellems Wire Management, Deluxe Cord Grips, Straight Male, 2.312-2.437", 2 1/2" with Mesh



Application

- Straight Male- Form 7

Performance

- Environmental - Flammability - UL 94HB (Strand grip), UL 94V-2(Fitting)
- Environmental - Hazardous Locations - Suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 N.E.C
- Environmental - Operating Temperatures - -30°F to +240°F (-34°C to +115°C)
- Environmental - Wet Locations - Suitable for use in wet locations when used with a listed sealing ring between box and fitting

General

Catalog Number	074011266
EU RoHS Indicator	Yes
Environmental Conditions	Suitable For Use In Wet Locations When Used With A Listed Sealing Ring Between Box And Fitting.
Item Type	Deluxe Cord Grips
Material	Aluminum Fittings, Stainless Steel Mesh
Material - Mounting Hardware	Locknut or Tapped Opening
Series	Deluxe Cord Grips
Specifications	<ul style="list-style-type: none">• Body - Aluminum

Style

Temperature Rating

Thread Size

Type

UPC

- Bushing - Neoprene
- Nut - Aluminum
- Strand - Stainless Steel

For Insulated Cables

Minimum -30 Deg F to 240 Deg F (-34 Deg C to 115 Deg C)

2 1/2" NPT

Straight Male Thread

783585498669

Dimensions

Display Size

2 1/2" NPT

Conductor Related

Cable Diameter Range

2.312 in-2.437 in

Cable Size

2.312"-2.437" (5.87-6.19)

Conductor Range

2.312-2.437 in (5.87-6.19 mm)

Number of Conductors

Single

Certifications And Compliance

Industry Standard(s)

UL Listed

Product Assets

[Catalogs - WDK Catalog Full 2024](#)

[Literature - Wire Management Solutions Brochure](#)

[Specifications - 74011266](#)

[Warranty - Industrial & Commercial Products](#)