

# Straight Blade Devices, Receptacles, Duplex, Commercial/Industrial Grade, 2- Pole 3-Wire Grounding, 15A 125V, 5- 15R, Ivory

By Hubbell Wiring Device-Kellems  
Catalog # 5262I



Straight Blade Devices, Receptacles, Duplex,  
Commercial/Industrial Grade, 2-Pole 3-Wire Grounding, 15A  
125V, 5-15R, Ivory

## Application

- Hubbell-Pro Extra Heavy Duty

## Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstands 2,000V minimum
- Environmental - Flammability - UL 94 V-2
- Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact)
- Mechanical - Product Identification - Ratings are a permanent part of the device
- Mechanical - Terminal Accommodation - #14-#10 AWG copper stranded or solid conductor only
- Mechanical - Terminal Identification - Terminal wire leads identified in accordance with UL 498

## General

Catalog Number	5262I
Color	Ivory
EU RoHS Indicator	Yes
Environmental Conditions	Indoor Dry unless protected by additional means
Horsepower - Maximum	0.5
Item Type	Traditional Duplex
Material	Thermoplastic/Composite
Material - Mounting Hardware	Screw Mounting
Mounting Type	Screw Mount
Number Of Poles	2-Pole
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Series	Hubbell-PRO
Size	Standard Sized Product
Specifications	<ul style="list-style-type: none"><li>• Automatic Self-grounding Staple - Stainless steel</li><li>• Base - PBT</li><li>• Contacts - Brass</li><li>• Face - Nylon</li></ul>

## Style

Temperature Rating

## Type

UPC

## Dimensions

Dimensions	3.28 in x 1.41 in x 1.09 in
Display Size	Standard Sized Product
Height	1.09 in
Length	3.28 in
Weight	0.55 lb
Width	1.41 in

## Electrical Ratings

Amperage Rating	15 A
Connectivity	Back and Side Wired
Current / Amperage Rating	15 A
Current Rating	15 A
Dielectric Strength	Withstands 2,000V minimum
Phase	Single Phase
Voltage Rating	125 V
Voltage Rating Description	125 V
Wattage	1875 W

## Conductor Related

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG

## Certifications And Compliance

Industry Standard(s)	UL File No. E2186, Certified to CSA 22.2, No. 42 File 285, Fed.
----------------------	---

- Mounting Screws - Zinc plated steel
  - Mounting Strap - Galvanized steel
- Finder Groove Face  
Maximum continuous 75°C;  
minimum -40°C (w/o impact)  
Standard Duplex  
783585650043

Nema Rating  
Standards - RoHS Compliance  
Status

Spec. W-C-596, NEMA® WD-6  
Compliant  
5-15R  
CM

Carton Quantity 10  
Pallet Quantity 4000

**Product Assets**

[Catalogs - WDK Catalog Full 2024](#)  
[Specifications - 5262I](#)  
[Warranty - Industrial & Commercial Products](#)

**Logistics**



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved  
WDK\_MX-5262I-SPEC-EN | REV 10/2024