HUBBELL Wiring Device-Kellems

Locking Devices, Twist-Lock®, Industrial, Receptacle, 50A 125/250V, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal, Black

By Hubbell Wiring Device-Kellems Catalog # CS6369

Locking Devices, Twist-Lock®, Industrial, Receptacle, 50A 125/250V, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal, Black

Performance

- Electrical Current Interrupting Certified for current interrupting at full rated current
- Electrical Dielectric Voltage Withstands 2,000V minimum
- Environmental Flammability UL 94 VO
- Environmental Operating Temperatures Maximum continuous 75°C minimum -40°C (w/o impact)
- Mechanical Terminal Accommodation #10 AWG #6 AWG solid or stranded copper wire only

General

Catalog Number CS6369 EU RoHS Indicator No

Environmental Conditions Indoor Dry Unless Protected By

Additional Means

Item Type Single Receptacle

Material Phenolic

Material - Mounting Hardware Screw Mounting

Number Of Poles 3-Pole

Operating Temperature Maximum continuous 75°C and

minimum -40°C without Impact
Specifications

• Body - Phenolic

• Contacts - Brass

• Face - Phenolic

Insulator - Phenolic

• Terminal Screws - Steel


Device

UPC 783585828107

Dimensions

Туре

Dimensions 2.69 in x 2.12 in x 2.36 in



 Height
 2.36 in

 Length
 2.69 in

 Weight
 0.8 lb

 Width
 2.12 in

Electrical Ratings

Amperage Rating 50 A

Connectivity Screw Terminals

Current Rating 50 A

Dielectric Strength Withstands 2,000V minimum

Phase Single Phase Voltage Rating 125/250 VAC Voltage Rating Description 125/250V AC

Conductor Related

Number Of Wires 4-Wire

Wire Size #10 AWG to #6 AWG

Certifications And Compliance

Industry Standard(s) • Certified to CSA C22.2

No.42

• Listed to UL 498

Logistics

Carton Quantity 10 Pallet Quantity 1600

Product Assets

Catalogs - WDK Catalog Full 2024

Specifications - CS6369

Warranty - Industrial & Commercial Products

