HUBBELL Wiring Device-Kellems

Locking Devices, Twist-Lock®, Industrial, Flanged Inlet, 50A, 125V, 2-Pole 3-Wire Grounding, Non-NEMA, Screw Terminal, Steel

By Hubbell Wiring Device-Kellems Catalog # CS6377

Locking Devices, Twist-Lock®, Industrial, Flanged Inlet, 50A, 125V, 2-Pole 3-Wire Grounding, Non-NEMA, Screw Terminal, Steel



Extra Heavy Duty Industrial

Performance

- Electrical Current Interrupting Certified for current interrupting at full rated current
- Electrical Dielectric Voltage Withstands 2,000V minimum
- Environmental Flammability UL 94 VO
- Environmental Operating Temperatures Maximum continuous 75°C minimum -40°C (w/o impact) Mechanical -Terminal Accommodation - #10 AWG - #6 AWG solid or stranded copper wire only

General

Catalog Number CS6377
Color Metallic
EU RoHS Indicator No

Environmental Conditions Indoor Dry Unless Protected By

Additional Means
Item Type Single Flanged Inlet
Material Steel, Zinc Plated
Material - Mounting Hardware Screw Mounting

Number Of Poles 2-Pole

Operating Temperature Maximum continuous 75°C and minimum -40°C without Impact

Specifications • Blades - Brass

Casing - Steel, zinc plated

• Terminal Retainer - Phenolic

• Terminal Screws - Steel

Type Flanged Inlet UPC 783585871356

Dimensions



Height 2.17 in
Length 3.5 in
Weight 0.8 lb
Width 2.62 in

Electrical Ratings

Amperage Rating 50 A

Connectivity Pressure Terminal Screws

Current / Amperage Rating 50 A
Current Rating 50 A

Dielectric Strength Withstands 2,000V minimum

Phase Single Phase

Voltage Rating 125 V Voltage Rating Description 125 V

Conductor Related

Number Of Wires 3-Wire

Wire Size #10 AWG to #6 AWG

Certifications And Compliance

Industry Standard(s) • Certified to CSA C22.2

No.42

• Listed to UL 498

Logistics

Carton Quantity 10

Product Assets

Catalogs - WDK Catalog Full 2024

Specifications - CS6377

Warranty - Industrial & Commercial Products

