Extra Heavy Duty Industrial Grade, Toggle Switches, General Purpose AC, Three Way, 15A 120/277V AC, Back and Side Wired Toggle

By Hubbell Wiring Device-Kellems Catalog # HBL1203I

Switches and Lighting Controls, Extra Heavy Duty Industrial Grade, Toggle Switches, General Purpose AC, Three Way, 15A 120/277V AC, Back and Side Wired, Ivory Toggle

Application

Back and Side Wired

Performance

- Electrical Dielectric Voltage Withstands 1500V AC minimum for 1 minute
- Electrical Max. Continuous Current 15A
- Electrical Max. Working Voltage 277V AC
- Electrical Overload Minimum 4.8 times rated current for 100 cycles
- Electrical Temperature Rise 30°C maximum at rated current
- Environmental Flammability UL 94V-2
- Environmental Operating Temperature Max. continuous: 75°C, Min. continuous: -40°C without impact
- Mechanical Terminal Accommodations #14 AWG min. #10 AWG max. solid and stranded copper wire only

General

Action	SPDT
Catalog Number	HBL1203I
Color	lvory
EU RoHS Indicator	No
Number Of Poles	Single Pole
Operating Temperature	Maximum continuous 75°C and
	minimum -40°C without Impact
Series	Extra Heavy Duty
Specifications	 Base Material - Thermoset,
	Blue
	 Contacts - Silver Alloy
	 Ground Screw - Brass
	(Green)
	 Terminal Screws - Brass

- Toggle Material Nylon
- Top Material Thermo
- Top Material Thermoset Three Way



Type UPC Toggle 783585430263

Dimensions

Dimensions4.06 in x 1.31 in x 1.87 inHeight1.87 inLength4.06 inWeight0.2 lbWidth1.31 in

Electrical Ratings

Amperage Rating	15 A
Connectivity	Back and Side Wired
Current / Amperage Rating	15 A
Current Rating	15 A
Dielectric Strength	Withstands 1500V AC minimum
	for 1 minute
Temperature Rise - Max.	30°C maximum at rated current
Voltage Rating	120-277 VAC
Voltage Rating Description	120-277 VAC

10

#14 AWG to #10 AWG

Conductor Related

Wire Size

Certifications And Compliance

Industry Standard(s) UL Listed

Logistics

Carton Quantity

Product Assets

Catalogs - WDK Catalog Full 2024 Specifications - HBL1203I Warranty - Industrial & Commercial Products



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved WDK_MX-HBL1203I-SPEC-EN | REV 10/2024