

Extra Heavy Duty Industrial Grade, Toggle Switches, General Purpose AC, Double Pole, 20A 120/277V AC, Back and Side Wired Toggle

By Hubbell Wiring Device-Kellems Catalog # HBL1222I

Switches and Lighting Controls, Extra Heavy Duty Industrial Grade, Toggle Switches, General Purpose AC, Double Pole, 20A 120/277V AC, Back and Side Wired, Ivory Toggle

Features

- · Large brass binding head screws with deep slots
- · Abuse resistant nylon toggle
- · Strip gauge for accurate wiring

Application

Back and Side Wired

General

Color

Number Of Poles Operating Temperature

Performance

- Ivory
- Ivoire

Double Pole

Maximum continuous 75°C and minimum -40°C without Impact

- Electrical Dielectric Voltage - Withstands 1500V AC minimum for 1 minute
- Electrical Max.
 Continuous Current 20A
- Electrical Max. Working Voltage - 277V AC
- Electrical Overload -Minimum 4.8 times rated current for 100 cycles
- Electrical Temperature Rise - 30°C maximum at rated current
- Environmental -Flammability - UL 94V-2
- Environmental Operating Temperature - Max. continuous: 75°C, Min. continuous: -40°C without impact
- Mechanical Terminal Accommodations - #14 AWG min. - #10 AWG max. solid and stranded copper wire only



Dimensions

Dimensions $4.06 \text{ in } \times 1.31 \text{ in } \times 1.87 \text{ in}$ Height 1.87 in

Length 4.06 in Weight 0.2 lb Width 1.31 in

Electrical Ratings

Amperage Rating 20 A

Connectivity Back and Side Wired

Current / Amperage Rating 20 A Current Rating 20 A

Dielectric Strength Withstands 1500V AC minimum for 1 minute

Temperature Rise - Max. 30°C maximum at rated

current

Voltage Rating 120-277 VAC Voltage Rating Description 120-277 VAC

Conductor Related

Wire Size #14 AWG to #10 AWG

Certifications and Compliance

Industry Standard(s) UL Listed

Logistics

Carton Quantity 10

Product Assets

Catalogs - WDK Catalog Full 2023 Warranty - Industrial & Commercial Products

Series Extra Heavy Duty

Type • Toggle • Toggle
UPC 783585431642



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved. WDK_MX-HBL1222I-SPEC-EN | REV 1/2024