

Extra Heavy Duty Industrial Grade, Locking Toggle Switches, General Purpose AC, Three Way, 20A 120/277V AC, Back and Side Wired **Key Guide**

By Hubbell Wiring Device-Kellems Catalog # HBL1223L

Switches and Lighting Controls, Extra Heavy Duty Industrial Grade, Locking Toggle Switches, General Purpose AC, Three Way, 20A 120/277V AC, Back and Side Wired, Black Key Guide

Features

- Large brass binding head screws with deep slots
- · Lock circuits On or Off
- Strip gauge for accurate wiring

Application

Back and Side Wired

General

Action Color

SPDT

Number Of Poles **Operating Temperature**

Performance

- Black
- Noir

Single Pole Maximum continuous 75°C

and minimum -40°C without Impact

- Electrical Dielectric Voltage - Withstands 1500V AC minimum for 1 minute
- Electrical Max. Continuous Current - 20A
- Electrical Max. Working Voltage - 277V AC
- Electrical Overload -• Minimum 4.8 times rated current for 100 cycles
- Electrical Temperature Rise - 30°C maximum at rated current
- Environmental -Flammability - UL 94V-2
- Environmental Operating Temperature - Max. continuous: 75°C, Min. continuous: -40°C without impact
- Mechanical Terminal Accommodations - #14 AWG min. - #10 AWG max. solid and stranded copper



Dimensions

Dimensions	4.06 in x 1.31 in x 1.13 in
Height	1.13 in
Length	4.06 in
Weight	0.2 lb
Width	1.31 in

Electrical Ratings

Amperage Rating	20 A
Connectivity	Back and Side Wired
Current / Amperage Rating	20 A
Current Rating	20 A
Dielectric Strength	Withstands 1500V AC minimum for 1 minute
Temperature Rise - Max.	30°C maximum at rated current
Voltage Rating	120-277 VAC
Voltage Rating Description	120-277 VAC
Conductor Related	
Wire Size	#14 AWG to #10 AWG

Wire Size

Certifications and Compliance

Industry Standard(s) **UL** Listed

Logistics

Carton Quantity 10

Product Assets

Catalogs - WDK Catalog Full 2023 Warranty - Industrial & Commercial Products wire only

Series Style Type UPC Extra Heavy Duty Three Way Locking 783585431888

HUBBELL

A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved. WDK_MX-HBL1223L-SPEC-EN | REV 1/2024