Switches and Lighting Controls, Industrial Grade, Toggle Switches, Motor Disconnects, Three Pole, 30A 600V AC

By Hubbell Wiring Device-Kellems Catalog # HBL1379D

Switches and Lighting Controls, Industrial Grade, Toggle Switches, Motor Disconnects, Three Pole, 30A 600V AC

Application

Standard Toggle

Performance

- Electrical Dielectric Voltage Min. 2,200V AC minimum for 1 minute
- Electrical Electrical Life Min. 6,000 Cycles at rated switch load
- Electrical Max. Working Voltage 600V AC RMS
- Environmental Flammability UL94HB/VO
- Environmental Operating Temperature Max. 75°C,Min.
 -40°C continuous w/o impact
- Mechanical Mechanical Life Min. 10,000 minimum cycles
- Mechanical Switch Rating 25 inch pounds
- Mechanical Terminal Accommodations #10 AWG Max
- Mechanical Terminal Torque 20 inch pounds
- Mechanical Wire Type Solid and stranded copper wire only

General

Catalog Number EU RoHS Indicator Enclosure Type

Environmental Conditions

Horsepower - Maximum Load Capacity Material - Mounting Hardware Operating Cycles Operating Temperature

Series Specifications Style Type HBL1379D Yes NEMA 1 Indoor Dry Unless Protected By Additional Means 15 Inductive Screw Mounting 10,000 Cycles Minimum Maximum continuous 75°C and minimum -40°C without Impact Non-Fused Enclosure Material - Aluminum Standard Duty Disconnect Switches



UPC

783585202617

Dimensions

Dimensions Display Size Height Length Weight Width

Standard Sized Product 3.15 in 4.52 in 1.05 lb 3.2 in

4.52 in x 3.2 in x 3.15 in

Electrical Ratings

Amperage Rating Connectivity Current / Amperage Rating Current Rating Dielectric Strength 30 A Pressure Terminal Screws 30 A 30 A 2,200V AC minimum for 1 minute Three Phase 18000 W

Phase Wattage

Certifications And Compliance

Industry Standard(s)

- CSA-C22.2 No.14 Industrial Control File LR-46186
 UL 508, Industrial Control
- File #E70402

10

Standards - RoHS Compliance Status

Logistics

Carton Quantity

Assots

Product Assets

Catalogs - WDK Catalog Full 2024 Specifications - HBL1379D



©2024 Hubbell Incorporated. All rights reserved WDK_MX-HBL1379D-SPEC-EN | REV 10/2024