

## Straight Blade Devices, Female Connector Body, Elasto-Grip Dust Tight, Industrial/Commercial Grade, Straight, 20A 125V, 5-20R

By Hubbell Wiring Device-Kellems  
Catalog # [HBL1533](#)



Straight Blade Devices, Female Connector Body, Elasto-Grip Dust Tight, Industrial/Commercial Grade, Straight, 2- Pole 3-Wire Grounding, 20A 125V, 5-20R, Yellow, Single Pack.

### Application

Industrial/Commercial

### Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstands 2,000V minimum
- Environmental - Flammability - UL 94 HB or better
- Environmental - IP Suitability - IP20
- Environmental - Operating Temperatures - Maximum continuous 75°C minimum -40°C (w/o impact)
- Mechanical - Terminal Accommodation - #18-12 AWG. Standed copper wire only
- Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

### General

Catalog Number	HBL1533
Color	Yellow
Cord Range	0.250"-0.655" (6.4-16.6)
EU RoHS Indicator	No
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Horsepower - Maximum	1
Insulation	Insulated Body
Item Type	Elastogrip
Material - Mounting Hardware	Cord Mounted
Number Of Poles	2-Pole
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Series	Elastogrip
Specifications	<ul style="list-style-type: none"> <li>• Assembly Screws - Plated steel</li> <li>• Contact Holder - Nylon</li> <li>• Contacts - .040 in. (1.0) Brass</li> <li>• Housing - Thermoplastic Elastomer</li> </ul>

### Style

Temperature Rating

### Type

UPC

### Dimensions

Dimensions	3.00 in x 1.61 in x 3.00 in
Display Size	Standard
Height	3 in
Length	3 in
Weight	0.15 lb
Width	1.61 in

### Electrical Ratings

Amperage Rating	20 A
Connectivity	Screw Terminals
Current / Amperage Rating	20 A
Current Rating	20 A
Dielectric Strength	Withstands 2,000V minimum
Phase	Single Phase
Voltage Rating	125 V
Voltage Rating Description	125 V

### Conductor Related

Conductor Range	#18 AWG to #12 AWG
Number Of Wires	3-Wire
Wire Size	#18 AWG to #12 AWG

### Certifications And Compliance

Industry Standard(s)	<ul style="list-style-type: none"> <li>• CSA Certified to C22.2 No. 42 File 280C</li> <li>• NEMA® WD-6 Compliant</li> </ul>
----------------------	---

- Terminal Clamp - Nickel plated steel
  - Terminal Retainer - Clear Polycarbonate
  - Terminal Screws - #8-32 Brass , multiple drive
- Standard  
Max Continuous- 75 Degrees C,  
Minimum- -40 Without Impact  
Connector Body  
783585013350

- UL Listed to UL498 File E1706

Pallet Quantity 4050

Nema Rating

5-20R

### Product Assets

### Logistics

Carton Quantity

10

[Catalogs - WDK Catalog Full 2024](#)

[Specifications - HBL1533](#)

[Warranty - Industrial & Commercial Products](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved  
WDK\_MX-HBL1533-SPEC-EN | REV 10/2024