Single Pole Products, Female Receptacle, Threaded Stud Termination, 150 Amp Series, White



By Hubbell Wiring Device-Kellems Catalog # HBL15FRSW

Single Pole Products, Female Receptacle, Threaded Stud Termination, 150 Amp Series, White

Features

- Threaded Stud Termination
- 150 Amp Series
- White

Application

Extra Heavy Duty Industrial

Performance

- Electrical Amperage Rating 150A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Mechanical Product Identification Ratings are a permanent part of device
- Mechanical Terminal Accommodation #8 to #2 AWG

General

Catalog Number
Color
EU RoHS Indicator
Environmental Conditions

Item Type Material Material - Mounting Hardware Number Of Poles Series Specifications

- HBL15FRSW White No Indoor Dry Unless Protected By Additional Means Female Receptacle Brass/Thermoplastic Screw Mounting 1-Pole Series 15 • Base Compound -
 - Thermoplastic Elastomer (TPE)
- Contact Material Brass
- Mounting Hole 3x Ø .20"
- Retaining Screw Material -Nylon
- Termination 5/16-18 Threaded Stud

Style		
Туре		
UPC		

Female Receptacle, Stud Type 783585458281

Dimensions

Display Size

Electrical Ratings

Standard Sized Product

150 A

150 A

150 A

90000

25

Threaded Stud

Single Phase

600V AC/DC

Amperage Rating Connectivity

Current / Amperage Rating Current Rating Phase Voltage Rating Description Wattage

Conductor Related

Number Of Wires Wire Size

Industry Standard(s)

None #4 AWG Type SC/PPC Wire

Certifications And Compliance

- National Electric Code (NEC), ANSI/NFPA 70
- UL and cUL Listed
- UL Enclosure Types 3R, 4X, 12
 Non-NEMA

Nema Rating

Logistics

Carton Quantity

Product Assets

Catalogs - WDK Catalog Full 2024 Literature - Single Pole Devices Specifications - HBL15FRSW Warranty - Industrial & Commercial Products

