

# Locking Devices, Twist-Lock®, Elastogrip® Connector, 15A, 125V, 2 Pole, 3 Wire Grounding, NEMA L5-15R, yellow elastomer, dust tight

By Hubbell Wiring Device-Kellems  
Catalog # [HBL2547](#)

Locking Devices, Twist-Lock®, Elastogrip® Connector, 15A, 125V, 2 Pole, 3 Wire Grounding, NEMA L5-15R, yellow elastomer, dust tight



## Application

Heavy Duty Industrial

## Performance

- Electrical-Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstand 2,000V minimum
- Mechanical - Terminal Accommodation - #18 AWG - #10 AWG stranded copper wire only
- Mechanical - Terminal Identification - Terminals identified in accordance with UL 498
- Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17
- Environmental - Moisture Resistance - IP20 Suitability
- Environmental - Operating Temperatures - Maximum Continuous 75°C
- Minimum -40°C (w/o impact)

## General

Catalog Number	HBL2547
Color	Yellow
Cord Range	0.300"-.655"(7.6-16.6)
EU RoHS Indicator	No
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Insulation	Insulated Body
Item Type	15A Elastogrip® Connector
Listings	<ul style="list-style-type: none"> <li>• UL 498</li> <li>• Fed.Spec. W-C-596</li> <li>• CSA C22.2 No.42</li> </ul>
Material	Elastomer / Elastomeric
Material - Mounting Hardware	Cord Mounted
Number Of Poles	2-Pole
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Specifications	<ul style="list-style-type: none"> <li>• Assembly Screws - Steel, zinc plated</li> <li>• Contacts - Brass</li> <li>• Cord Clamp - Nylon</li> </ul>

Temperature Rating

UPC

## Dimensions

Dimensions	4.00 in x 1.76 in x 4.00 in
Display Size	Standard
Height	4 in
Length	4 in
Weight	0.2 lb
Width	1.76 in

## Electrical Ratings

Amperage Rating	15 A
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	15 A
Current Rating	15 A
Dielectric Strength	Withstands 2,000V minimum
Voltage Rating	125 VAC
Voltage Rating Description	125 VAC

## Conductor Related

Number Of Wires	3-Wire Grounding
Wire Size	#18 AWG to #10 AWG

## Certifications And Compliance

Industry Standard(s)	<ul style="list-style-type: none"> <li>• Certified to CSA C22.2 No.42</li> <li>• Fed.Spec. W-C-596</li> <li>• Listed to UL 498</li> </ul>
Nema Rating	L5-15R

## Logistics

- Cord Clamp Screws - Steel, zinc plated
  - Terminal Retainer - Clear polycarbonate
  - Terminal Screws - Brass
- Maximum Continuous: 75° C;  
Minimum Continuous: -40° C w/o impact, -25° with impact.  
783585235905

Carton Quantity

10

Catalogs - WDK Catalog Full 2024

Specifications - HBL2547

Warranty - Industrial & Commercial Products

**Product Assets**



**A Hubbell brand**

©2024 Hubbell Incorporated. All rights reserved  
WDK\_MX-HBL2547-SPEC-EN | REV 10/2024