

# Locking Devices, Twist-Lock®, Marine Grade, Hull Inlet, 30A 125V, 2-Pole 3-Wire Grounding, L5-30P, Screw Terminal, Stainless Steel

By Hubbell Wiring Device-Kellems  
Catalog # [HBL303SS](#)



Locking Devices, Twist-Lock®, Marine Grade, Hull Inlet, 30A 125V, 2-Pole 3-Wire Grounding, L5-30P, Screw Terminal, Stainless Steel

## General

Application	Marine Wiring Devices
Catalog Number	HBL303SS
Color	Stainless
EU RoHS Indicator	Yes
Environmental Conditions	Watertight
Insulation	Insulated Body
Item Type	Hull Mount Single
Material	Thermoplastic
Material - Mounting Hardware	Screw Hull Mount
Number Of Poles	2-Pole
Performance	Environmental - Moisture Resistance - IP56 Suitability
Temperature Rating	Maximum Continuous: 75° C; Minimum Continuous: -40° C w/o impact
UPC	783585040523

## Dimensions

Display Size	Standard Sized Product
--------------	------------------------

## Electrical Ratings

Amperage Rating	30 A
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	30 A
Current Rating	30 A
Dielectric Strength	Withstands 3000V Minimum in Single Phase
Phase	Single Phase
Voltage Rating	125 VAC
Wattage	3750

## Conductor Related

Number Of Wires	3-Wire Grounding
Wire Size	#12 AWG to #10 AWG

## Certifications And Compliance

Industry Standard(s)	UL Listed
Nema Rating	L5-30P
Standards - RoHS Compliance Status	CM

## Logistics

Carton Quantity	5
Pallet Quantity	455

## Product Assets

- [Catalogs - WDK Catalog Full 2024](#)
- [Warranty - Industrial & Commercial Products](#)
- [Video - Hubbell Marine Products](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved  
WDK\_MX-HBL303SS-SPEC-EN | REV 6/2024