

## Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Female, Receptacle, 30A 250V AC, 2-Pole 3- Wire Grounding, Watertight

By Hubbell Wiring Device-Kellems  
Catalog # [HBL330R6W](#)

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Female, Receptacle, 30A 250V AC, 2-Pole 3- Wire Grounding, Terminal Screws, Blue, Watertight



### Application

- High Ampacity Watertight Connections

### Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - 3000V AC
- Electrical - Max. Working Voltage - 600V RMS
- Electrical - Temperature Rise - Max. 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%
- Environmental - Flammability - HB or better per UL 94 or CSA C22.2 No. 0.17
- Environmental - Ingress Protection - IP67 Suitability
- Environmental - Moisture Resistance - Watertight per IEC 60309-1
- Environmental - Operating Temperatures - Maximum Continuous 75°C
- Minimum - 40°C w/o impact
- Mechanical - Impact Resistance - Per CSA C22.2 No.182.1 /UL1682
- Mechanical - Product Identification - Identification and ratings are a permanent part of the device housing
- Mechanical - Terminal Identification - Terminals identified in accordance with North American and IEC conventions

### General

Catalog Number	HBL330R6W
Color	Blue
EU RoHS Indicator	Yes
Environmental Conditions	Watertight
Item Type	Single Flanged
Material	Thermoplastic
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
Series	HBL Heavy Duty
Specifications	<ul style="list-style-type: none"> <li>• Cover - Reinforced Thermoplastic Polyester</li> </ul>

- Cover Screw - Nickel-plated brass
  - Gaskets - Solid Neoprene
  - Housing - Zytel® 101 Nylon
  - Mounting Flange - Zytel® 101 Nylon
- Standard Service  
Watertight Receptacle  
783585403625

Style  
Type  
UPC

### Dimensions

Display Size Standard Sized Product

### Electrical Ratings

Amperage Rating	30 A
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	30 A
Current Rating	30 A
Phase	Single Phase
Voltage Rating	250 VAC
Voltage Rating Description	250 VAC
Wattage	7500

### Conductor Related

Number Of Wires	3-Wire
Wire Size	#12 AWG to #8 AWG

### Certifications And Compliance

Industry Standard(s)	<ul style="list-style-type: none"> <li>• CSA Standard C22.2 No. 182.1</li> <li>• UL Classified to IEC 60309-1 IEC 60309-2</li> <li>• UL Listed, File E146032</li> </ul>
Nema Rating	Non-NEMA

### Logistics

Carton Quantity	1
Pallet Quantity	640



A Hubbell brand