

## Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Female, Mechanically Interlocked Receptacle, 60A 250V AC, Watertight

By Hubbell Wiring Device-Kellems  
Catalog # [HBL360MI6W](#)

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Female, Mechanically Interlocked Receptacle, 60A 250V AC, 2-Pole 3-Wire Grounding, Terminal Screws, Blue, Watertight

### Application

High Ampacity Watertight Connections

### Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current and voltage
- Electrical - Dielectric Voltage - Withstands 3,000V AC Min
- Electrical - Max. Working Voltage - 600V AC RMS
- Environmental - Flammability - UL94-5VA and V-0 Classification
- Environmental - Ingress Protection - IP67 Suitability
- Environmental - Moisture Resistance - Outdoor - 4X (Watertight, Washdown)
- Indoor - 12 (Dust-tight, Falling Dirt and Noncorrosive Liquids).
- Environmental - Operating Temperature - Max. Continuous +75°C
- Min. Continuous -40°C
- Mechanical - Impact Resistance - In accordance with UL 746C
- Mechanical - Mounting - External adjustable feet
- Mechanical - Product Identification - Identification and ratings are part of the external label and molded into the receptacle mount
- Mechanical - Terminal Identification - In accordance with UL, CSA and international conventions

### General

Catalog Number	HBL360MI6W
Color	Blue
EU RoHS Indicator	No
Environmental Conditions	Watertight
Item Type	Mechanically Interlocked Single
Material	Thermoplastic
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
Series	Non-Fused
Specifications	<ul style="list-style-type: none"> <li>• Base - Valox®</li> <li>• Conduit Hub - Zinc</li> </ul>



Style  
Type  
UPC

- Enclosure Gasket - Neoprene
  - Face - Valox®
  - Shaft Seal - Neoprene
- Standard Service  
Mechanical Interlock  
783585405858

### Dimensions

Display Size Standard Sized Product

### Electrical Ratings

Amperage Rating	60 A
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	60 A
Current Rating	60 A
Phase	Single Phase
Voltage Rating	240 VAC
Voltage Rating Description	240 VAC
Wattage	15000

### Conductor Related

Number Of Wires	3-Wire
Wire Size	#8 AWG to #2 AWG

### Certifications And Compliance

Industry Standard(s)	UL Listed
Nema Rating	Non-NEMA

### Logistics

Carton Quantity	1
Pallet Quantity	84

### Product Assets

[Catalogs - WDK Catalog Full 2024](#)  
[Specifications - HBL360MI6W](#)



**A Hubbell brand**