Locking Devices, Twist-Lock[®], Industrial, Receptacle, 50A 250V DC/600V AC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw **Terminal, Phenolic, Black**

By Hubbell Wiring Device-Kellems Catalog # HBL3769

Locking Devices, Twist-Lock®, Industrial, Receptacle, 50A 250V DC/600V AC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal, Phenolic, Black

Performance

- Electrical Current Interrupting Certified for current interrupting at full rated current
- Electrical Dielectric Voltage Withstands 2,000V minimum
- Environmental Flammability V2 or better per UL94/CSA 22.2 No.0.17
- Environmental Operating Temperatures Maximum Continuous 75°C Minimum -40°C (w/o impact)
- Mechanical Terminal Accommodation #10 AWG #6 AWG solid or stranded copper wire only

General

Catalog Number EU RoHS Indicator **Environmental Conditions**

Item Type Material Material - Mounting Hardware Number Of Poles Operating Temperature

Specifications

Туре UPC

Dimensions

Dimensions **Display Size** HBL3769 No Indoor Dry Unless Protected By Additional Means **50A Receptacle** Phenolic Screw Mounting 3-Pole Maximum continuous 75°C and minimum -40°C without Impact • Body - Phenolic

- Contacts Brass
- Face Phenolic
- Insulator Phenolic

 Terminal Screws - Steel Receptacle 783585236469

3.28 in x 2.12 in x 2.36 in Standard Sized Product



| Height | 2.36 in |
|--------|---------|
| _ength | 3.28 in |
| Weight | 0.75 lb |
| Width | 2.12 in |
| | |

Electrical Ratings

H

L

ν

V

| Amperage Rating | 50 A |
|----------------------------|---------------------------|
| Connectivity | Screw Terminals |
| Current / Amperage Rating | 50 A |
| Current Rating | 50 A |
| Dielectric Strength | Withstands 2,000V minimum |
| Phase | Multi Phase |
| Voltage Rating | 250 VDC/600 VAC |
| Voltage Rating Description | 250 VDC/600 VAC |
| Voltage Rating | 250 VDC/600 VAC |

Conductor Related

| Number Of Wires | 4-Wire |
|-----------------|------------------|
| Wire Size | #8 AWG to #4 AWG |

Certifications And Compliance

| Industry Sta | ndard(s) |
|--------------|----------|
|--------------|----------|

- No.42
 - Listed to UL 498

• Certified to CSA C22.2

Logistics

Carton Quantity Pallet Quantity

10 1000

Product Assets

Catalogs - WDK Catalog Full 2024 Specifications - HBL3769 Warranty - Industrial & Commercial Products

