#### HUBBELL Wiring Device-Kellems

# Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Female, Mechanically Interlocked Receptacle, 20A 3-Phase Delta 480V AC,

By Hubbell Wiring Device-Kellems Catalog # HBL420MI7W

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Female, Mechanically Interlocked Receptacle, 20A 3-Phase Delta 480V AC, 3-Pole 4-Wire Grounding, Terminal Screws



High Ampacity Watertight Connections

#### **Performance**

- Electrical Current Interrupting Certified for current interrupting at full rated current and voltage
- Electrical Dielectric Voltage Withstands 3,000V AC Min
- Electrical Max. Working Voltage 600V AC RMS
- Environmental Flammability UL94-5VA and V-O Classification
- Environmental Ingress Protection IP67 Suitability
- Environmental Moisture Resistance Outdoor 4X (Watertight, Washdown)
- Indoor 12 (Dust-tight, Falling Dirt and Noncorrosive Liquids).
- Environmental Operating Temperature Max. Continuous +75°C
- Min. Continuous -40°C
- Mechanical Impact Resistance In accordance with UL 746C
- Mechanical Mounting External adjustable feet
- Mechanical Product Identification Identification and ratings are part of the external label and molded into the receptacle mount
- Mechanical Terminal Identification In accordance with UL, CSA and international conventions

#### General

Catalog Number HBL420MI7W
Color Red
EU RoHS Indicator No
Environmental Conditions Watertight

Item TypeMechanically Interlocked SingleMaterialThermoplastic

Material - Mounting Hardware Screw Mounting
Number Of Poles 3-Pole

Series Non-Fu Specifications • Base

Thermoplastic
Screw Mounting
3-Pole
Non-Fused

Base - Valox®Conduit Hub - Zinc



• Enclosure Gasket -Neoprene

• Face - Valox®

 Shaft Seal - Neoprene Standard Service
 Mechanical Interlock
 783585392899

**Dimensions** 

Style

Type

UPC.

Display Size Standard Sized Product

### **Electrical Ratings**

Amperage Rating 20 A

Connectivity Pressure Terminal Screws

Current / Amperage Rating 20 A
Current Rating 20 A
Phase Three Phase
Voltage Rating 3 Phase 480 VAC
Voltage Rating Description 3 Phase 480 VAC

Wattage 9600

Conductor Related

Number Of Wires 4-Wire

Wire Size #14 AWG to #10 AWG

## **Certifications And Compliance**

Industry Standard(s) UL Listed
Nema Rating Non-NEMA

Logistics

Carton Quantity 1

#### **Product Assets**

Catalogs - WDK Catalog Full 2024 Specifications - HBL420MI7W



©2025 Hubbell Incorporated. All rights reserved WDK\_MX-HBL420MI7W-SPEC-EN | REV 1/2025