## HUBBELL Wiring Device-Kellems

# Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Female, Mechanically Interlocked Receptacle, 60A 3-Phase Delta 600V AC,

By Hubbell Wiring Device-Kellems Catalog # HBL460MI5W

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Female, Mechanically Interlocked Receptacle, 60A 3-Phase Delta 600V AC, 3-Pole 4-Wire Grounding, Terminal Screws

## **Application**

• High Ampacity Watertight Connections

## Performance

- Electrical Current Interrupting Certified for current interrupting at full rated current and voltage
- Electrical Dielectric Voltage Withstands 3,000V AC Min
- Electrical Max. Working Voltage 600V AC RMS
- Environmental Flammability UL94-5VA and V-0 Classification
- Environmental Ingress Protection IP67 Suitability
- Environmental Moisture Resistance Outdoor 4X (Watertight, Washdown)
- Indoor 12 (Dust-tight, Falling Dirt and Noncorrosive Liquids).
- Environmental Operating Temperature Max. Continuous +75°C
- Min. Continuous -40°C
- Mechanical Impact Resistance In accordance with UL 746C
- Mechanical Mounting External adjustable feet
- Mechanical Product Identification Identification and ratings are part of the external label and molded into the receptacle mount
- Mechanical Terminal Identification In accordance with UL, CSA and international conventions

#### General

Specifications

Catalog Number HBL460MI5W Color Noir **EU RoHS Indicator** No **Environmental Conditions** Watertight Item Type Mechanically Interlocked Single Thermoplastic Material Material - Mounting Hardware Screw Mounting Number Of Poles 3-Pole Series Non-Fused

• Base - Valox®

· Conduit Hub - Zinc

CIRCUIT-LOCK

For a function of the control of the

Neoprene

Face - Valox®

Neoprene

• Enclosure Gasket -

Standard Service Mechanical Interlock 783585406046

## **Dimensions**

Style

Type

**UPC** 

Display Size Standard Sized Product

## **Electrical Ratings**

Amperage Rating 60 A
Connectivity Pressure Terminal Screws
Current / Amperage Rating 60 A
Current Rating 60 A
Phase Three Phase
Voltage Rating 3 Phase 600 VAC
Voltage Rating Description 3 Phase 600 VAC

36000

## **Conductor Related**

Wattage

Number Of Wires 4-Wire

Wire Size #8 AWG to #2 AWG

## **Certifications And Compliance**

Industry Standard(s) UL Listed
Nema Rating Non-NEMA

## Logistics

Carton Quantity 1
Pallet Quantity 84

#### **Product Assets**

Catalogs - WDK Catalog Full 2024



©2024 Hubbell Incorporated. All rights reserved WDK\_MX-HBL460MI5W-SPEC-EN | REV 10/2024