HUBBELL Wiring Device-Kellems

Locking Devices, Twist-Lock®, Industrial, Flush Receptacle, 15A 277V AC, 2-Pole 3-Wire Grounding, L7-15R, Screw Terminal, Brown, Product Mod

By Hubbell Wiring Device-Kellems Catalog # HBL4760C

Locking Devices, Twist-Lock®, Industrial, Single Flush Receptacle, 15A 277V AC, 2-Pole 3-Wire Grounding, NEMA L7-15R, Screw Terminal, Black Nylon face.



General

Material

Application Heavy Duty Industrial

HBL4760C Catalog Number

EU RoHS Indicator No

Environmental Conditions Indoor Dry Unless Protected By

2

Additional Means

Horsepower - Maximum

Item Type 15A Grounding Single Flush

Receptacle Thermoplastic

Material - Mounting Hardware Screw Mounting

2-Pole Number Of Poles

Operating Temperature Maximum continuous 75°C and

minimum -40°C without Impact

Performance Electrical - Current Interrupting

> - Certified for current interrupting at full rated

current

Electrical - Dielectric Voltage -Withstands 2,000V minimum

Environmental - Flammability -HB or better per UL94/CSA

22.2 No.0.17

Environmental - Operating Temperatures - Maximum Continuous 75°C. Minimum -40°C (w/o impact)

Mechanical - Terminal

Accommodation - #18 AWG -#10 AWG solid or stranded

copper wire only.

Mechanical - Terminal Identification - Terminals identified in accordance with

UL 498

Туре Receptacle UPC 783585093345

Dimensions

Dimensions 3.28 in x 1.53 in x 1.27 in Standard Sized Product Display Size

Height 1.27 in Length 3.28 in 0.2 lb Weight Width 1.53 in

Electrical Ratings

15 A Amperage Rating

Connectivity Back and Side Wired

Current / Amperage Rating 15 A Current Rating 15 Δ

Dielectric Strength Withstands 2,000V minimum

Single Phase Phase Voltage Rating 277 VAC Voltage Rating Description 277 VAC

Conductor Related

Number Of Wires 3-Wire

Wire Size #18 AWG to #10 AWG

Certifications And Compliance

Industry Standard(s) Certified to CSA C22.2 No.42

СМ

Fed. Spec. W-C-596

Listed to UL 498

Standards - RoHS Compliance

Status

Logistics

100 Carton Quantity

Product Assets

Catalogs - WDK Catalog Full 2024

Warranty - Industrial & Commercial Products



©2024 Hubbell Incorporated. All rights reserved WDK_MX-HBL4760C-SPEC-EN | REV 6/2024