Surge Protective Devices, SPIKESHIELD TVSS Duplex Receptacle with Light, 15A 125V, 5-15R, White

By Hubbell Wiring Device-Kellems Catalog # HBL5260WSA

Surge Protective Devices, SPIKESHIELD TVSS Duplex Receptacle with Light, 15A 125V, 5-15R, White

Application

Decorator Duplex

Performance

- Electrical Protection Modes Normal and Common Modes
- Electrical Response Time Approximately 5 ns
- Electrical Transient Suppression Peak Energy (10 X 100 Qs), Peak Current (8 X 20 Qs)
- Electrical Voltage 120V AC + 10% 15%
- Environmental Flammability UL 94V-2
- Environmental Operating Temperature 32°F to 140°F (0°C to 60°C)

General

Ca

Catalog Number	HBL5260WSA
Color	White
EU RoHS Indicator	No
Environmental Conditions	Indoor Dry Unless Pro
	Additional Means
Indicator(s) Type	None
Item Type	Surge Protection Rec
Material	Composite
Material - Mounting Hardware	Mounting Screws
Operating Temperature	32 Deg F to 140 Deg
	C to 60 Deg C)

Outlet **Response Time** Series Specifications

otected By ceptacles F (0 Deg Straight Blade 5

Specification Grade

- Base Material Nylon Contact Design - Tandem Modified Bypass
- Face Material Nylon
- Mounting Strap .050" (1.3) Steel-Zinc Coated



• Power Contact - .031" (.8) Brass Duplex 783585219905

Standard

Terminal Screws

15 A

15 A

15 A

60 Hz

125 V

125 V

Single Phase

Dimensions

Display Size

Туре

UPC

Electrical Ratings

Amperage Rating Connectivity Current / Amperage Rating Current Rating Frequency Rating Phase Voltage Rating Voltage Rating Description

Certifications And Compliance

Levistics	
Nema Rating	5-15R
	UL Listed File E2186
	• Listed to UL Standards 498
	Specification C22.2 No. 42
Industry Standard(s)	CSA Certified to

10

Logistics

Carton Quantity

Product Assets

Catalogs - WDK Catalog Full 2024 Literature - Residential Catalog Specifications - HBL5260WSA Warranty - Industrial & Commercial Products

