

Surge Protective Devices, SPIKESHIELD TVSS Duplex Receptacle with Light and Alarm, 15A 125V, 5-15R, Blue

By Hubbell Wiring Device-Kellems Catalog # HBL5262SA

Surge Protective Devices, SPIKESHIELD TVSS Duplex Receptacle with Light and Alarm, 15A 125V, 5-15R, Blue



- Automatic self-grounding staple
- Distinctive surge symbol provides quick identification
- Power-on indicator light verifies that power is available
- Alert alarm sounds when surge protection is no longer functioning

Application

Decorator Duplex with Light and Alarm

General

Color

Bleu

Bleu

Environmental Conditions

Indicator(s) Type Item Type Material Material - Mounting Hardware

Operating Temperature

Outlet Performance Indoor Dry Unless Protected By Additional Means LED and Audible Alarm Surge Protection Receptacles Composite Mounting Screws 32 Deg F to 140 Deg F (O Deg C to 60 Deg C)

 Electrical - Protection Modes - Normal and Common Modes

Straight Blade

- Electrical Response Time Approximately 5 ns
- Electrical Transient
 Suppression Peak Energy
 (10 X 100 μs), Peak Current
 (8 X 20 μs)
- Electrical Voltage 120V AC + 10% - 15%
- Environmental -Flammability - UL 94V-2
- Environmental Operating Temperature - 32°F to 140°F (0°C to 60°C)

Response Time

Series Specification Grade

Type • Duplex • Duplex

Dimensions

Display Size Standard

Electrical Ratings

Amperage Rating 15 A

Connectivity Terminal Screws

Current / Amperage Rating 15 A
Current Rating 15 A
Frequency Rating 60 Hz
Phase Single Phase
Voltage Rating 125 V

Voltage Rating Description 125 V

Certifications and Compliance

Industry Standard(s) • CSA Certified to

Specification C22.2 No. 42

• Listed to UL Standards 498

• UL Listed File E2186

Nema Rating 5-15R

Logistics

Carton Quantity 10

Product Assets

Catalogs - WDK Catalog Full 2023 Warranty - Industrial & Commercial Products A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved. WDK_MX-HBL5262SA-SPEC-EN | REV 1/2024