

Straight Blade Devices, **Receptacles, Duplex, Commercial** Grade, 2-Pole 3-Wire Grounding, 15A 277V AC, 7-15R, Brown, Single Pack

By Hubbell Wiring Device-Kellems Catalog # HBL5302

Straight Blade Devices, Receptacles, Duplex, Commercial Grade, 2-Pole 3-Wire Grounding, 15A 277V AC, 7-15R, Brown, Single Pack.

Application

• Heavy Duty

General

Color **EU RoHS Indicator Environmental Conditions**

Horsepower - Maximum Item Type Material Material - Mounting Hardware Number Of Poles **Operating Temperature**

Performance

| | • Brown | |
|---|---|--|
| | Yes | |
| | Indoor Dry Unless Protected By Additional Means 2 | |
| | z Single | |
| | Thermoplastic | |
| Э | Screw Mounting | |
| | 2-Pole | |
| | Maximum continuous 75°C and minimum -40°C without Impact | |
| | • Electrical - Current Interrupting - Certified for current interrupting at full rated current | |
| | Electrical - Dielectric Voltage - Withstands 2,000V minimum | |
| | • Environmental - Flammability - UL 94 V-0 | |
| | | |

• Environmental - Operating Temperatures - Maximum continuous 75°C minimum -40°C (w/o impact)

- Mechanical Product Identification - Ratings are a permanent part of the device
- Mechanical Terminal Accommodation - #14-#10 AWG copper stranded or solid conductor only
- Mechanical Terminal Identification - Terminals identified in accordance with UL 498 and CSA



Dimensions

| Dimensions | 3.28 in x 1.33 in x 1.19 in |
|--------------|-----------------------------|
| Display Size | Standard Sized Product |
| Height | 1.19 in |
| Length | 3.28 in |
| Weight | 0.25 lb |
| Width | 1.33 in |
| | |

15 A

15 A

15 A

277 V

4155 W

Single Phase 277 VAC

Back and Side Wired

Withstands 2,000V minimum

Electrical Ratings

Amperage Rating Connectivity Current / Amperage Rating Current Rating **Dielectric Strength** Phase Voltage Rating Voltage Rating Description Wattage

Conductor Related

| Number Of Wires | 3-Wire |
|-----------------|--------------------|
| Wire Size | #14 AWG to #10 AWG |

| Certifications And Compliance | | | | |
|---------------------------------------|---|--|--|--|
| Industry Standard(s) | • CSA Certified to C22.2 No. 42 File 280C | | | |
| | NEMA[®] WD-6 Compliant | | | |
| | UL Listed to UL498 File E1706 | | | |
| Nema Rating | 7-15R | | | |
| Standards - RoHS Compliance Status | СМ | | | |

10

Logistics

Carton Quantity

Product Assets

Catalogs - WDK Catalog Full 2024 Warranty - Industrial & Commercial Products

| 001103 | Extra neavy Daty |
|--------|------------------|
| Туре | Standard Duplex |
| | Standard Duplex |
| UPC | 783585014241 |



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved. WDK_MX-HBL5302-SPEC-EN | REV 5/2024