

Surge Protective Devices, SPIKESHIELD TVSS Duplex Receptacle with Light and Alarm, 20A 125V, 5-20R, Ivory

By Hubbell Wiring Device-Kellems Catalog # HBL5362ISA

Surge Protective Devices, SPIKESHIELD TVSS Duplex Receptacle with Light and Alarm, 20A 125V, 5-20R, Ivory



Application

Decorator Duplex with Light and Alarm

General

Color

1.......

Environmental Conditions

Indicator(s) Type Item Type Material

Material - Mounting Hardware Operating Temperature

Outlet

Performance

Ivory

Ivoire

Indoor Dry Unless Protected By Additional Means LED and Audible Alarm Surge Protection Receptacles

Composite

Mounting Screws

32 Deg F to 140 Deg F (0 Deg C to 60 Deg C)

Straight Blade

 Electrical - Protection Modes - Normal and Common Modes

Electrical - Response Time
 Approximately 5 ns

Electrical - Transient
 Suppression - Peak Energy
 (10 X 100 μs), Peak Current
 (8 X 20 μs)

 Electrical - Voltage - 120V AC + 10% - 15%

 Environmental -Flammability - UL 94V-2

 Environmental - Operating Temperature - 32°F to 140°F (0°C to 60°C)

Response Time 5

Series Specification Grade

Duplex

Duplex

UPC 783585060279

Dimensions

Display Size Standard

Electrical Ratings

Amperage Rating 20 A

Connectivity Terminal Screws

Current / Amperage Rating 20 A
Current Rating 20 A
Frequency Rating 60 Hz
Phase Single Phase

Voltage Rating 125 V Voltage Rating Description 125 V

Certifications and Compliance

Industry Standard(s) • CSA Certified to

Specification C22.2 No. 42

• Listed to UL Standards 498

• UL Listed File E2186

Nema Rating 5-20R

Logistics

Carton Quantity 10

Product Assets

Catalogs - WDK Catalog Full 2023 Warranty - Industrial & Commercial Products



Type