#### HUBBELL Wiring Device-Kellems

# Locking Devices, Twist-Lock®, Industrial, Flanged Receptacle, 15A 2-Pole 2-Wire Non Grounding, L1-15R, Screw Terminal, White

By Hubbell Wiring Device-Kellems Catalog # HBL7526

Locking Devices, Twist-Lock®, Industrial, Flanged Receptacle, 15A 125V 2-Pole 2-Wire Non Grounding, NEMA L1-15R, Screw Terminal, Stainless steel casing, Black/Stainless.



Heavy Duty Industrial

#### **Performance**

- Electrical Current Interrupting Certified for current interrupting at full rated current
- Electrical Dielectric Voltage Withstands 2,000V minimum
- Environmental Flammability HB or better per UL94/CSA 22.2 No.0.17
- Environmental Moisture Resistance IP20 Suitability
- Environmental Operating Temperatures Maximum Continuous 75°C, Minimum -40°C (w/o impact)
- Mechanical Terminal Accommodation #18 AWG #10 AWG solid or stranded copper wire only.
- Mechanical Terminal Identification Terminals identified in accordance with UL 498

## General

Catalog Number HBL7526 **EU RoHS Indicator Environmental Conditions** Indoor Dry Unless Protected By Additional Means Horsepower - Maximum Item Type 15A Non-Grounding Flanged Receptacles Material Nylon Material - Mounting Hardware Screw Mounting Number Of Poles 2-Pole Operating Temperature Maximum continuous 75°C and minimum -40°C without Impact

Specifications

• Contacts - Brass
• Flange - Stainless steel

 Mounting Screw - Nickel plated brass

• Terminal Screws - Brass

Type Flanged Inlet UPC 783585237565



#### **Dimensions**

 $\begin{array}{ll} \mbox{Dimensions} & 2.03 \mbox{ in x 1.63 in x 1.06 in} \\ \mbox{Display Size} & \mbox{Standard Sized Product} \\ \mbox{Height} & 1.06 \mbox{ in} \\ \mbox{Length} & 2.03 \mbox{ in} \end{array}$ 

Length2.03 inWeight0.1 lbWidth1.63 in

### **Electrical Ratings**

Amperage Rating 15 A

Connectivity Screw Terminals

Current / Amperage Rating 15 A
Current Rating 15 A

Dielectric Strength Withstands 2,000V minimum

Phase Single Phase

Voltage Rating 125 V Voltage Rating Description 125 V

## **Conductor Related**

Number Of Wires 2-Wire

Wire Size #18 AWG to #10 AWG

#### **Certifications And Compliance**

Industry Standard(s) Listed to UL 498

Nema Rating L1-15R Standards - RoHS Compliance CM

Status

## Logistics

Carton Quantity 10

#### **Product Assets**

Catalogs - WDK Catalog Full 2024 Specifications - HBL7526

Warranty - Industrial & Commercial Products

