

Locking Devices, Twist-Lock[®], Industrial, Flanged Inlet, 50A 250V DC/600V AC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal

By Hubbell Wiring Device-Kellems Catalog # HBL7968

Locking Devices, Twist-Lock®, Industrial, Flanged Inlet, 50A 250V DC/600V AC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal, Zinc plated steel casing, thermoset interior with lift cover, Metallic

Features

- Metallic flanged casing provides maximum strength and protection
- Thermoset interior provides superior heat resistance

Application

Extra Heavy Duty Industrial

General

Color **Environmental Conditions**

Item Type Material Material - Mounting Hardware Number Of Poles **Operating Temperature**

Performance

Metallic Indoor Dry Unless Protected By Additional Means 50A Flanged Inlet Steel, Zinc Plated Screw Mounting 3-Pole Maximum continuous 75°C and minimum -40°C without Impact

- Electrical Current Interrupting - Certified for current interrupting at full rated current
- Electrical Dielectric Voltage - Withstands 2,000V minimum
- Environmental -Flammability - UL 94 VO
- Environmental Operating Temperatures - Maximum continuous 75°C minimum -40°C (w/o impact)
- Mechanical Terminal Accommodation - #10 AWG - #6 AWG solid or stranded copper wire only

Flanged Inlet

783585237879



Dimensions

Dimensions	2.17 in x 3.50 in x 2.68 in
Display Size	Standard Sized Product
Height	2.68 in
Length	2.17 in
Weight	1.10 lb
Width	3.50 in

Electrical Ratings

Amperage Rating	50 A
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	50 A
Current Rating	50 A
Dielectric Strength	Withstands 2,000V minimum
Phase	Three Phase
Voltage Rating	250 VDC/600 VAC
Voltage Rating Description	250 VDC/600 VAC

Conductor Related

Number Of Wires Wire Size

4-Wire #8 AWG to #4 AWG

Certifications and Compliance

Industry Standard(s)

- Certified to CSA C22.2 No.42
- Listed to UL 498

10

Logistics

Carton Quantity

Product Assets

Catalogs - WDK Catalog Full 2023 Warranty - Industrial & Commercial Products

