Heavy Duty Products, Single Pole Devices, Industrial Grade, Female, Receptacle, 300/400A 600V AC/DC, Single Conductor, Set Screw, Blue



By Hubbell Wiring Device-Kellems Catalog # HBLFRBL

Heavy Duty Products, Single Pole Devices, Industrial Grade, Female, Receptacle, 300/400A 600V AC/DC, Single Conductor, Set Screw, Blue

Features

- Industrial Grade
- Female
- Receptacle

Application

High Ampacity Connections

Performance

- Electrical Amperage Rating 400A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Environmental Flammability HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification Ratings are a permanent part of device
- Mechanical Terminal Accommodation #4 to 4/0 AWG

General

Catalog Number	HBLFRBL
Color	Blue
EU RoHS Indicator	Yes
Environmental Conditions	Indoor Dry Unless Protected By
	Additional Means
Item Type	Panel Mount Receptacle
Material	Elastomer / Elastomeric
Material - Mounting Hardware	Threaded Thru-Hole
Number Of Poles	1-Pole
Series	Series 16
Specifications	 Base Compound -
	Thermoplastic Elastomer
	 Contact Material - Brass

- Mounting Hole 4x #10-32
- Retaining Screw Material -Nylon
- Termination (2) 7/32 Socket Head Set Screws Female Double Set Screw

Type UPC Receptacle 783585112602

Standard Sized Product

Dimensions

Display Size

Electrical Ratings

Amperage Rating400 AConnectivityScrew TerminalsCurrent / Amperage Rating400 ACurrent Rating400 APhaseSingle PhaseVoltage Rating Description600V AC/DCWattage240000

Conductor Related

Number Of Wires	1-Wire
Wire Size	#4 AWG to #4/0 AWG

Certifications And Compliance

Industry Standard(s)	 National Electric Code (NEC), ANSI/NFPA 70 UL and cUL Listed UL Enclosure Types 3R, 4X, 12
Nema Rating	Non-NEMA
Logistics	
Carton Quantity	25
Pallet Quantity	16128
Product Assets	
Product Assets	

Catalogs - WDK Catalog Full 2024 Literature - Single Pole Devices Specifications - HBLFRBL Warranty - Industrial & Commercial Products

Style



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved WDK_MX-HBLFRBL-SPEC-EN | REV 10/2024