HUBBELL Wiring Device-Kellems

Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Receptacle, 300/400A 600V AC/DC, Single Conductor, Set Screw, Red

By Hubbell Wiring Device-Kellems Catalog # HBLFRR

Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Receptacle, 300/400A 600V AC/DC, Single Conductor, Set Screw, Red



Features

- · Industrial Grade
- Female Receptacle
- 300/400A 600V AC/DC

Application

High Ampacity Connections

Performance

- Electrical Amperage Rating 400A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Environmental Flammability HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification Ratings are a permanent part of device
- Mechanical Terminal Accommodation #4 to 4/0 AWG

General

Catalog Number HBLFRR
Color Red
EU RoHS Indicator Yes

Environmental Conditions Indoor Dry Unless Protected By

Additional Means

Item TypePanel Mount ReceptacleMaterialElastomer / ElastomericMaterial - Mounting HardwareThreaded Thru-Hole

Number Of Poles 1-Pole

Series Series 16

Specifications • Base Compound -

Thermoplastic Elastomer

- Contact Material Brass
- Mounting Hole 4x #10-32
- Retaining Screw Material -Nylon
- Termination (2) 7/32
 Socket Head Set Screws

Style Female Double Set Screw

Type Receptacle UPC 783585112640

Dimensions

Display Size Standard Sized Product

Electrical Ratings

Amperage Rating 400 A

Connectivity Double Set Screw

Current / Amperage Rating 400 A
Current Rating 400 A
Phase Single Phase
Voltage Rating Description 600V AC/DC
Wattage 240000

Conductor Related

Number Of Wires 1-Wire

Wire Size #4 AWG to #4/0 AWG

Certifications And Compliance

Industry Standard(s) • National Electric Code

(NEC), ANSI/NFPA 70
• UL and cUL Listed

• UL Enclosure Types 3R, 4X,

12

Nema Rating Non-NEMA

Logistics

Carton Quantity 25 Pallet Quantity 1575

Product Assets

Catalogs - WDK Catalog Full 2024 Literature - Single Pole Devices Specifications - HBLFRR

Warranty - Industrial & Commercial Products

