Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Receptacle, 300/400A 600V AC/DC, Single Conductor, Threaded Stud, Orange



By Hubbell Wiring Device-Kellems Catalog # HBLFRSO

Heavy Duty Single Pole Industrial Grade, Female Receptacle, 300/400A 600V AC/DC, Single Conductor, Threaded Stud

General

Application Catalog Number Color EU RoHS Indicator Environmental Conditions Item Type Material Material - Mounting Hardware Number Of Poles Performance	High Ampacity Connections HBLFRSO Orange Yes Indoor Dry Unless Protected By Additional Means Panel Mount Receptacle Elastomer / Elastomeric Threaded Thru-Hole 1-Pole Electrical - Amperage Rating - 400A Maximum
	Electrical - Voltage Ratings - 600V AC Maximum
	250V DC Maximum
	Environmental - Flammability - HB per UL94 or CSA 22.2. 0.17
	Mechanical - Product Identification - Ratings are a permanent part of device
	Mechanical - Terminal Accommodation - #4 to 4/0 AWG
Series	Series 16
Style	Stud Type, Through Hole Mounting, Female
Type UPC	Receptacle 783585112695

Electrical Ratings

Amperage Rating	400 A
Connectivity	Stud Type
Current / Amperage Rating	400 A
Current Rating	400 A
Phase	Single Phase
Voltage Rating Description	600V AC/DC
Wattage	240000

Conductor Related

Number Of Wires	
Wire Size	

1-Wire #4 AWG to #4/0 AWG

Certifications And Compliance

Industry Standard(s)	National Electric Code (NEC), ANSI/NFPA 70
	UL and cUL Listed
	UL Enclosure Types 3R, 4X, 12
Nema Rating	Non-NEMA
Logistics	
Carton Quantity Pallet Quantity	25 1575

Product Assets

Catalogs - WDK Catalog Full 2024 Literature - Single Pole Devices Warranty - Industrial & Commercial Products

Dimensions Display Size

Standard Sized Product



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved WDK_MX-HBLFRSO-SPEC-EN | REV 6/2024