Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Receptacle, 300/400A 600V AC/DC, Single Conductor, Threaded Stud, Yellow



By Hubbell Wiring Device-Kellems Catalog # HBLFRSY

Heavy Duty Single Pole Industrial Grade, Female Receptacle, 300/400A 600V AC/DC, Single Conductor, Threaded Stud

Features

- Industrial Grade
- Female Receptacle
- 300/400A 600V AC/DC

Application

High Ampacity Connections

Performance

- Electrical Amperage Rating 400A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Environmental Flammability HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification Ratings are a permanent part of device
- Mechanical Terminal Accommodation #4 to 4/0 AWG

General

Catalog Number	HBLFRSY	(
Color	Yellow	
EU RoHS Indicator	Yes	I
Environmental Conditions	Indoor Dry Unless Protected By	
	Additional Means	
Item Type	Panel Mount Receptacle	
Material	Elastomer / Elastomeric	
Material - Mounting Hardware	Threaded Thru-Hole	1
Number Of Poles	1-Pole	
Series	Series 16	l
Specifications	Base Compound -	
	Thermoplastic Elastomer	ſ
	Contact Material - Brass	ł
	 Mounting Hole - 4x Ø .20" 	
	Retaining Screw Material -	1
	Nylon	(
	 Termination - 1/2-13 UNC-2A 	l
	Threaded Stud	9
Style		١
Style	Stud Type, Through Hole	

Mounting, Female

Туре UPC

Receptacle 783585112725

Standard Sized Product

Dimensions

Display Size

Electrical Ratings

400 A Amperage Rating Connectivity Stud Type Current / Amperage Rating 400 A Current Rating 400 A Phase Single Phase Voltage Rating Description 600V AC/DC 240000 Wattage

Conductor Related

Number Of Wires	1-Wire
Wire Size	#4 AWG to #4/0 AWG

Certifications And Compliance

Industry Standard(s)	 National Electric Code (NEC), ANSI/NFPA 70 UL and cUL Listed UL Enclosure Types 3R, 4X, 12
Nema Rating	Non-NEMA
Logistics	
Carton Quantity Pallet Quantity	25 1575
Product Assets	

Catalogs - WDK Catalog Full 2024 Literature - Single Pole Devices Specifications - HBLFRSY Warranty - Industrial & Commercial Products

HUBBELL

A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved WDK MX-HBLFRSY-SPEC-EN | REV 10/2024