Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Receptacle, 300/400A, 600V AC/DC, Single Conductor, Set Screw, White



By Hubbell Wiring Device-Kellems Catalog # HBLFRW

Heavy Duty Products, Single Pole Devices, Industrial Grade, Female Receptacle, 300/400A, 600V AC/DC, Single Conductor, Set Screw, White

Features

- Industrial Grade
- Female Receptacle
- 300/400A

Application

High Ampacity Connections

Performance

- Electrical Amperage Rating 400A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Environmental Flammability HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification Ratings are a permanent part of device
- Mechanical Terminal Accommodation #4 to 4/0 AWG

General

Catalog Number	HBLFRW
Color	White
EU RoHS Indicator	Yes
Environmental Conditions	Indoor Dry Unless Protected By
	Additional Means
Item Type	Panel Mount Receptacle
Material	Elastomer / Elastomeric
Material - Mounting Hardware	Threaded Thru-Hole
Number Of Poles	1-Pole
Series	Series 16
Specifications	 Base Compound -
	Thermoplastic Elastomer
	 Contact Material - Brass
	 Mounting Hole - 4x #10-32

- Retaining Screw Material -Nylon
- Termination (2) 7/32 Socket Head Set Screws Double Set Screw Female

Туре UPC

Receptacle 783585112732

Standard Sized Product

Dimensions

Display Size

Electrical Ratings

400 A Amperage Rating Connectivity Double Set Screw Current / Amperage Rating 400 A Current Rating 400 A Single Phase Phase Voltage Rating Description 600V AC/DC 240000 Wattage

Conductor Related

Number Of Wires	1-Wire
Wire Size	#4 AWG to #4/0 AWG

Certifications And Compliance

Industry Standard(s) Nema Rating	 National Electric Code (NEC), ANSI/NFPA 70 UL and cUL Listed UL Enclosure Types 3R, 4X, 12 Non-NEMA
Logistics	
Carton Quantity Pallet Quantity	25 1575
Product Assets	

Catalogs - WDK Catalog Full 2024 Literature - Single Pole Devices Specifications - HBLFRW Warranty - Industrial & Commercial Products

Style

HUBBELL

A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved WDK_MX-HBLFRW-SPEC-EN | REV 10/2024