HUBBELL Wiring Device-Kellems

Heavy Duty Products, Single Pole Devices, Industrial Grade, Male, Receptacle, 300/400A 600V AC/DC, Single Conductor, Set Screw, Red

By Hubbell Wiring Device-Kellems Catalog # HBLMRR

Heavy Duty Products, Single Pole Devices, Industrial Grade, Male, Receptacle, 300/400A 600V AC/DC, Single Conductor, Set Screw, Red



Features

- Industrial Grade
- Male
- Receptacle

Application

High Ampacity Connections

Performance

- Electrical Amperage Rating 400A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Environmental Flammability HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification Ratings are a permanent part of device
- Mechanical Terminal Accommodation #4 to 4/0 AWG

General

Catalog Number HBLMRR
Color Red
EU RoHS Indicator Yes

Environmental Conditions Indoor Dry Unless Protected By

Additional Means

Item TypeFlanged SingleMaterialThermoplasticMaterial - Mounting HardwareScrew Mounting

Number Of Poles 1-Pole
Series Series 1

Series Series 16
Specifications • Base 0

 Base Compound -Thermoplastic Elastomer

• Contact Material - Brass

• Mounting Hole - 4x #10-32

 Retaining Screw Material -Nylon

Termination - (2) 7/32
 Socket Head Set Screws

Style Double Set Screw Male

Type Receptacle UPC 783585112985

Dimensions

Display Size Standard Sized Product

Electrical Ratings

Amperage Rating 400 A

Connectivity Screw Terminals

Current / Amperage Rating 400 A
Current Rating 400 A
Phase Single Phase
Voltage Rating Description 600V AC/DC

Conductor Related

Wattage

Wire Size #4 AWG to #4/0 AWG

Certifications And Compliance

Industry Standard(s) • National Electric Code

(NEC), ANSI/NFPA 70
• UL and cUL Listed

• UL Enclosure Types 3R, 4X,

12

240000

Nema Rating Non-NEMA

Logistics

Carton Quantity 25
Pallet Quantity 1575

Product Assets

Catalogs - WDK Catalog Full 2024 Literature - Single Pole Devices Specifications - HBLMRR

Warranty - Industrial & Commercial Products

