Heavy Duty Products, Single Pole Devices, Industrial Grade, Male, Receptacle, 300/400A 600V AC/DC, Single Conductor, Threaded Stud, Black



By Hubbell Wiring Device-Kellems Catalog # HBLMRSBK

Heavy Duty Products, Single Pole Devices, Industrial Grade, Male, Receptacle, 300/400A 600V AC/DC, Single Conductor, Threaded Stud, Black

Features

- Industrial Grade
- Male
- Receptacle

Application

High Ampacity Connections

Performance

- Electrical Amperage Rating 400A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Environmental Flammability HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification Ratings are a permanent
 part of device
- Mechanical Terminal Accommodation #4 to 4/0 AWG

General

Series

Specifications

Catalog Number
Color
EU RoHS Indicator
Environmental Conditions
Item Type
Material
Material - Mounting Hardware
Number Of Poles

HBLMRSBK Black Yes Indoor Dry Unless Protected By Additional Means Flanged Single Thermoplastic Screw Mounting 1-Pole Series 16

- Base Compound Thermoplastic Elastomer
- Contact Material Brass
- Mounting Hole 4x Ø .20"
- Retaining Screw Material Nylon
- Termination 1/2-13 UNC-2A Threaded Stud

Style

Type UPC

Stud Type, Through Hole Mounting, Male Receptacle 783585112992

Dimensions Display Size

Standard Sized Product

Screw Terminals

Single Phase

600V AC/DC

400 A

400 A

400 A

240000

Electrical Ratings

Amperage Rating Connectivity Current / Amperage Rating Current Rating Phase Voltage Rating Description Wattage

Conductor Related

Certifications And Compliance

Wire Size

Industry Standard(s)

#4 AWG to #4/0 AWG

National Electric Code (NEC), ANSI/NFPA 70
UL and cUL Listed
UL Enclosure Types 3R, 4X, 12
Non-NEMA

Logistics

Nema Rating

Carton Quantity	25
Pallet Quantity	1575

Product Assets

Catalogs - WDK Catalog Full 2024 Literature - Single Pole Devices Specifications - HBLMRSBK



©2025 Hubbell Incorporated. All rights reserved WDK_MX-HBLMRSBK-SPEC-EN | REV 1/2025