HUBBELL Wiring Device-Kellems

Heavy Duty Products, Single Pole Devices, Industrial Grade, Male, Receptacle, 300/400A, 600V AC/DC, Single Conductor, Threaded Stud, Blue

By Hubbell Wiring Device-Kellems Catalog # HBLMRSBL

Heavy Duty Products, Single Pole Devices, Industrial Grade, Male, Receptacle, 300/400A, 600V AC/DC, Single Conductor, Threaded Stud, Blue

Features

- Industrial Grade
- Male
- Receptacle

Application

High Ampacity Connections

Performance

- Electrical Amperage Rating 400A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Environmental Flammability HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification Ratings are a permanent part of device
- Mechanical Terminal Accommodation #4 to 4/0 AWG

General

Catalog Number **HBLMRSBL** Color Blue **EU RoHS Indicator Environmental Conditions** Indoor Dry Unless Protected By Additional Means Item Type Flanged Single Material Thermoplastic Material - Mounting Hardware Screw Mounting Number Of Poles 1-Pole Series Series 16 Specifications • Base Compound -

 Base Compound -Thermoplastic Elastomer

- Contact Material Brass
- Mounting Hole 4x Ø .20"
- Retaining Screw Material -
- Termination 1/2-13 UNC-2A Threaded Stud



Style Stud Type, Through Hole

Mounting, Male
Type Receptacle
UPC 783585113005

Dimensions

Display Size Standard Sized Product

Electrical Ratings

Amperage Rating 400 A
Connectivity Screw Terminals
Current / Amperage Rating 400 A
Current Rating 400 A
Phase Single Phase
Voltage Rating Description 600V AC/DC

Voltage Rating Description 600V AC/D Wattage 240000

Conductor Related

Wire Size #4 AWG to #4/0 AWG

Certifications And Compliance

Industry Standard(s) • National Electric Code

(NEC), ANSI/NFPA 70

UL and cUL Listed

UL Enclosure Types 3R, 4X,

12

Nema Rating Non-NEMA

Logistics

Carton Quantity 25 Pallet Quantity 1575

Product Assets

Catalogs - WDK Catalog Full 2024 Literature - Single Pole Devices Specifications - HBLMRSBL



©2024 Hubbell Incorporated. All rights reserved WDK_MX-HBLMRSBL-SPEC-EN | REV 10/2024