## HUBBELL Wiring Device-Kellems

# **Heavy Duty Products, Single Pole Devices, Industrial Grade, Male Receptacle, 300/400A 600V** AC/DC, Single Conductor, Threaded **Mounting Holes**

By Hubbell Wiring Device-Kellems Catalog # HBLMRSCBL

Heavy Duty Products, Single Pole Devices, Industrial Grade, Male Receptacle, 300/400A 600V AC/DC, Single Conductor, Threaded Mounting Holes, Stud Termination, Blue

# **Features**

- · Industrial Grade
- Male Receptacle
- 300/400A 600V AC/DC

## **Application**

**High Ampacity Connections** 

#### Performance

- Electrical Amperage Rating 400A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Environmental Flammability HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification Ratings are a permanent part of device
- Mechanical Terminal Accommodation #4 to 4/0 AWG

#### General

Catalog Number Color Blue **EU RoHS Indicator Environmental Conditions** Item Type Material Screw Mounting Material - Mounting Hardware Number Of Poles 1-Pole Series Series 16 Specifications

**HBLMRSCBL** 

Indoor Dry Unless Protected By

Additional Means Flanged Single Thermoplastic

• Base Compound -Thermoplastic Elastomer

- Contact Material Brass
- Mounting Hole 4x Ø .20"
- Retaining Screw Material -
- Termination 1/2-13 UNC-2A Threaded Stud



Style Stud Type, Threaded Hole

Mounting, Male Type Receptacle **UPC** 783585093536

## **Dimensions**

Display Size Standard Sized Product

## **Electrical Ratings**

Amperage Rating 400 A

Screw Terminals Connectivity

Current / Amperage Rating 400 A **Current Rating** 400 A Phase Single Phase Voltage Rating Description 600V AC/DC 240000 Wattage

## **Conductor Related**

Wire Size #4 AWG to #4/0 AWG

# **Certifications And Compliance**

Industry Standard(s) National Electric Code

> (NEC), ANSI/NFPA 70 • UL and cUL Listed

• UL Enclosure Types 3R, 4X, 12

Nema Rating Non-NEMA

# Logistics

Carton Quantity 25 Pallet Quantity 1575

#### **Product Assets**

Catalogs - WDK Catalog Full 2024 Literature - Single Pole Devices Specifications - HBLMRSCBL



©2025 Hubbell Incorporated. All rights reserved WDK\_MX-HBLMRSCBL-SPEC-EN | REV 1/2025