HUBBELL Wiring Device-Kellems

Heavy Duty Products, Single Pole Devices, Industrial Grade, Male Receptacle, 300/400A 600V AC/DC, Single Conductor, Threaded **Mounting Holes**

By Hubbell Wiring Device-Kellems Catalog # HBLMRSCBL

Heavy Duty Products, Single Pole Devices, Industrial Grade, Male Receptacle, 300/400A 600V AC/DC, Single Conductor, Threaded Mounting Holes, Stud Termination, Blue

Features

- Industrial Grade
- Male Receptacle
- 300/400A 600V AC/DC

Application

High Ampacity Connections

Performance

- Electrical Amperage Rating 400A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Environmental Flammability HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification Ratings are a permanent part of device
- Mechanical Terminal Accommodation #4 to 4/0 AWG

General

Catalog Number Color Blue **EU RoHS Indicator** Yes **Environmental Conditions** Indoor Dry Unless Protected By Additional Means Item Type Flanged Single Material Thermoplastic Material - Mounting Hardware Screw Mounting Number Of Poles

Series Series 16

Specifications

HBLMRSCBL

1-Pole

• Base Compound -Thermoplastic Elastomer

- Contact Material Brass
- Mounting Hole 4x Ø .20"
- · Retaining Screw Material -
- Termination 1/2-13 UNC-2A Threaded Stud

Style Stud Type, Threaded Hole

Mounting, Male Receptacle Туре UPC 783585093536

Dimensions

Display Size Standard Sized Product

Electrical Ratings

400 A Amperage Rating

Connectivity Screw Terminals

Current / Amperage Rating 400 A **Current Rating** 400 A Phase Single Phase

Voltage Rating Description 600V AC/DC Wattage 240000

Conductor Related

Wire Size #4 AWG to #4/0 AWG

Certifications And Compliance

Industry Standard(s) · National Electric Code

(NEC), ANSI/NFPA 70

• UL and cUL Listed

• UL Enclosure Types 3R, 4X,

12

Nema Rating Non-NEMA

Logistics

Carton Quantity 25 Pallet Quantity 1575

Product Assets

Catalogs - WDK Catalog Full 2024 Literature - Single Pole Devices Specifications - HBLMRSCBL



©2024 Hubbell Incorporated. All rights reserved WDK_MX-HBLMRSCBL-SPEC-EN | REV 10/2024