HUBBELL Wiring Device-Kellems

Heavy Duty Products, Single Pole Devices, Industrial Grade, Male Receptacle, 300/400A 600V AC/DC, Single Conductor, Threaded Stud, Red

By Hubbell Wiring Device-Kellems Catalog # HBLMRSR

Heavy Duty Products, Single Pole Devices, Industrial Grade, Male Receptacle, 300/400A 600V AC/DC, Single Conductor, Threaded Stud, Red

Features

- Industrial Grade
- Male Receptacle
- 300/400A 600V AC/DC

Application

High Ampacity Connections

Performance

- Electrical Amperage Rating 400A Maximum
- Electrical Voltage Ratings 600V AC Maximum
- 250V DC Maximum
- Environmental Flammability HB per UL94 or CSA 22.2. 0.17
- Mechanical Product Identification Ratings are a permanent part of device
- Mechanical Terminal Accommodation #4 to 4/0 AWG

General

Catalog Number **HBLMRSR** Color Red **EU RoHS Indicator Environmental Conditions** Indoor Dry Unless Protected By Additional Means Item Type Flanged Single Material Thermoplastic Material - Mounting Hardware Screw Mounting Number Of Poles 1-Pole Series Series 16 Specifications • Base Compound -Thermoplastic Elastomer

• Contact Material - Brass

 Mounting Hole - 4x Ø .20" · Retaining Screw Material -

• Termination - 1/2-13 UNC-2A

Threaded Stud

Style Stud Type, Through Hole

Mounting, Male Receptacle Туре UPC 783585113043

Dimensions

Display Size Standard Sized Product

Electrical Ratings

400 A Amperage Rating Connectivity Screw Terminals Current / Amperage Rating 400 A **Current Rating** 400 A Phase Single Phase Voltage Rating Description 600V AC/DC Wattage 240000

Conductor Related

Wire Size #4 AWG to #4/0 AWG

Certifications And Compliance

Industry Standard(s) · National Electric Code

(NEC), ANSI/NFPA 70 • UL and cUL Listed

• UL Enclosure Types 3R, 4X,

12

Nema Rating Non-NEMA

Logistics

Carton Quantity 25 Pallet Quantity 1575

Product Assets

Catalogs - WDK Catalog Full 2024 Literature - Single Pole Devices Specifications - HBLMRSR



©2024 Hubbell Incorporated. All rights reserved WDK_MX-HBLMRSR-SPEC-EN | REV 10/2024