

Surge Protective Devices, **SPIKESHIELD Hospital Grade** Surge Suppression Receptacle, 20A 125V, 5-20R, Ivory

By Hubbell Wiring Device-Kellems Catalog # IG8362ISA

Surge Protective Devices, SPIKESHIELD Hospital Grade Surge Suppression Receptacle, 20A 125V, 5-20R, Ivory



- High-impact nylon face resists breakage
- · Automatic grounding clip attached to bridge
- Power-on indicator light verifies instantly that power is available
- Distinctive surge symbol provides quick visual identification of surge suppression receptacle

Application

Decorator Duplex with Light and Alarm

General

Color

Ivory

Environmental Conditions

Indicator(s) Type Item Type Material Material - Mounting Hardware

Operating Temperature

Outlet Performance

Ivoire

Indoor Dry Unless Protected By Additional Means

LED and Audible Alarm Surge Protection Receptacles

Composite

Mounting Screws

32 Deg F to 140 Deg F (O Deg C to 60 Deg C)

Straight Blade

• Electrical - Frequency -

- Electrical Protection Modes - Normal and Common Modes
- Electrical Response Time - Approximately 5 ns
- Electrical Transient Suppression - Peak Energy (10 X 100 μ s) Peak Current $(8 \times 20 \mu s)$
- Electrical Voltage 120V AC + 10% - 15%
- Environmental -Flammability - UL 94V-2
- Environmental Operating Temperature - 32°F to 140°F (0°C to 60°C)



Dimensions

Display Size Standard

Electrical Ratings

20 A Amperage Rating

Connectivity Terminal Screws

Current / Amperage Rating 20 A Current Rating 20 A Frequency Rating 60 Hz Phase Single Phase

125 V Voltage Rating Voltage Rating Description 125 V

Certifications and Compliance

Industry Standard(s)

· CSA Certified to Specification C22.2 No. 42

• Listed to UL Standards 498

Receptacles

• UL Listed File E2186

Nema Rating 5-20R

Logistics

Carton Quantity 10

Product Assets

Catalogs - WDK Catalog Full 2023 Warranty - Industrial & Commercial Products Series Hospital Grade
Style Isolated Ground
Type • Duplex
• Duplex

UPC 783585060934



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved. WDK_MX-IG8362ISA-SPEC-EN | REV 1/2024