HUBBELL Wiring Device-Kellems

Non-Metallic Raceway, BaseTrak, 2 or 3 Channel, External Elbow, Base and Cover

By Hubbell Wiring Device-Kellems Catalog # PB3EEBCA

Non-Metallic Raceway, BaseTrak, 2 or 3 Channel, External Elbow, Base and Cover



• Full capacity 11/4 in. bend radius external elbow

Application

External Elbow Base and Cover

Performance

- Environmental Flame Rating UL94V-0
- Environmental Temperature Range -25.6° to 158° F

General

Series

Catalog Number PB3EEBCA
Color Office White
Cover Type Removable
EU RoHS Indicator Contact Manufacturer
Item Type PB2 and PB3 BaseTrak Series
Material Non-Metallic

Non-Metallic
PB2
PB3



• Crush Resistance - 300 lbs.

Impact Resistance - 5 ft. lbs.
 Material - LIV Stabilized RVC

Material - UV Stabilized PVC

Style External

Sub Brand Non-Metallic Raceway

Type Elbows

UPC 783585310084

Certifications And Compliance

Industry Standard(s) UL 5A Standards - RoHS Compliance CM

Status

Logistics

Carton Quantity 10

Product Assets

Catalogs - WDK Catalog Full 2024 Specifications - PB3EEBCA

Warranty - Industrial & Commercial Products