Hubbell-PRO

63 A, 220-240 VAC, 2-POLE, 3-WIRE

Watertight Receptacle

HUBBELL

Features

- · IP67 environmental ratings
- Impact and corrosion resistant insulated non-metallic housing
- Sequential contact engagement to prevent a momentary over-voltage
- Color coded housings provide quick identification of mating devices

Ordering Information

Description Heavy Duty Products, IEC Pin and Sleeve Devices, Hubbell-PRO, Female, Receptacle

Color Blue

UPC 783585676012

Catalog Number C363R6WA

Listings


VDE, CE

Specifications

High Ampacity Connections Application Connection Pressure Screw Terminal Wire Size #6AWG to #4AWG PBT Material

Mounting

Screw Mount



Complementary Products

Complementary Products

Adapter Plate, Back Box

Performance

Electrical

Withstand 3000V AC Dielectric Voltage Max. Working Voltage 600V AC RMS

Mechanical

Impact Resistance Per CSA C22.2 No. 182.1 / UL1682

Product Identification Identification and ratings are marked on device

housing

Terminal Identification Terminals identified in accordance with North

American and IEC conventions

Environmental

Flammability HB IP67 Ingress Protection Moisture Resistance IEC 60309-1

Temperature Rating Maximum Continuous: 75° C: Minimum

Continuous: -40° C w/o impact, -25° with impact.

Online Resources

Customer Sales Drawings

eCatalog

Installation Instructions

