Hubbell-PRO 60/63 A, 120/208 VAC, 4-POLE, 5-WIRE Splash Proof Receptacle



- IP44 environmental ratings
- · Impact and corrosion resistant insulated non-metallic housing
- Sequential contact engagement to prevent a momentary over-voltage
- Color coded housings provide quick identification of mating devices

Ordering Information

DescriptionColorHeavy Duty Products, IECBluePin and Sleeve Devices,Hubbell-PRO, Female,ReceptacleKeceptacle


UPC Number Catalog Number 783585679426 C560R9SA


Listings

All constructions are UL Listed & cUL Listed FileE14632

Specifications

Application Connection Wire Size Material Mounting High Ampacity Connections Pressure Screw Terminal #6AWG to #4AWG PBT Screw Mount





Complementary Products

Complementary Products

Adapter Plate, Back Box

Performance

Electrical Dielectric Voltage Max. Working Voltage

Mechanical

Impact Resistance Product Identification

Terminal Identification

Environmental

Flammability Ingress Protection Moisture Resistance Temperature Rating Withstand 3000V AC 600V AC RMS

HΒ

Per CSA C22.2 No. 182.1 / UL1682 Identification and ratings are marked on device housing Terminals identified in accordance with North American and IEC conventions

IP44 IEC 60309-1 Maximum Continuous: 75° C; Minimum Continuous: -40° C w/o impact, -25° with impact.

Online Resources

Customer Sales Drawings eCatalog Installation Instructions



Wiring Device-Kellems

