Ground Fault Products Heavy Duty Commercial Tamper-Resistant and Weather Resistant GFCI Receptacles

HUBBELL

Features

- Patented shutter design for tamper-resistant protection
- Meets NEC requirements for weather resistance (406.9), UV and corrosion resistance for harsh and damp applications
- Patented AUTOGUARD® self test technology
- Protects against line and load reversal, no power to the face or downstream if device is miswired
- Single LED status indicator green indicates power, red indicates a trip, flashing red indicates end
 of life

Ordering Information

Description Color UPC Catalog Number 20A, 125V, Style Gray 883778999376 GFRTW20GRY Line®, AUTOGUARD® self test GFCI receptacle, tamper-resistant and weather resistant, flush face, back and side wired, tri-drive screws



Listings

UL Listed - Canadian and U.S. UL 943 Class A for GFCIs UL File E41978 Meets ADA Standards Meets all NEC® and CEC requirements CSA Certified NEMA® WD-6 ANSI 73 Compliant

Specifications

Face Nylon
Base Nylon
Power Contacts Brass
Ground Contacts Brass
Mounting Strap

Mounting Strap Zinc plated steel
Mounting Screws Zinc plated steel
Auto-Ground Staple Stainless steel

Performance

Electrical

Current Interrupting Certified for current interrupting at full rated current

Dielectric Voltage Current

Trip Level Withstands 1,500V minimum

Trip Time 4 to 6 mA

np rime .025 second nominal

Frequency 60 Hz

Voltage 120V AC +10% - 15% (102V to 132V)

Amperage 15A/20A, 20A Feed Thru

Maximum Interrupting Capacity 10,000A

Mechanical

Product Identification Ratings are a permanent part of the device Terminal Accommodation #14-#10 AWG copper stranded or solid

conductor only

Terminal Identification Terminals identified in accordance with UL

498 and CSA

Environmental

Flammability UL 94V-2

Operating Temperature -35°C to 66°C or -30°F to 150°F

Accessories

Wallplates for duplex openings

Online Resources

Customer Use Drawing eCatalog

Installation Instructions

