# Ground Fault Products Heavy Duty Commercial Weather Resistant GFCI Receptacles

# HUBBELL

#### **Features**

- Patented AUTOGUARD® self test technology
- Meets NEC requirements for weather resistance (406.9), UV and corrosion resistance for harsh and damp applications
- Protects against line and load reversal, no power to the face or downstream if device is miswired

Catalog Number GFRWR15GRY

 Single LED status indicator - green indicates power, red indicates a trip, flashing red indicates end of life

# **Ordering Information**

Description Color UPC
15A, 125V, Style Gray 883778999727
Line®,
AUTOGUARD® self
test GFCI receptacle,
weather resistant,
flush face, back and
side wired, tri-drive
screws



### Listings

UL Listed - Canadian and U.S.
UL 943 Class A for GFCIs UL File E41978
Meets ADA Standards
Meets all NEC® and CEC requirements
CSA Certified
NEMA® WD-6 ANSI 73 Compliant

# **Specifications**

Face Nylon
Base Nylon
Power Contacts Brass
Ground Contacts Brass

Mounting Strap

Mounting Screws

Auto-Ground Staple

Zinc plated steel

Zinc plated steel

Stainless steel

# **Performance**

# Electrical

Current Interrupting Certified for current interrupting at full rated

Dielectric Voltage current
Trip Level Withstands 1,500V minimum

4 to 6 mA

Trip Time .025 second nominal

Frequency 60 Hz

Voltage 120V AC +10% - 15% (102V to 132V)

Amperage 15A/20A, 20A Feed Thru

Maximum Interrupting Capacity 10,000A

#### Mechanical

Product Identification Ratings are a permanent part of the device Terminal Accommodation #14-#10 AWG copper stranded or solid

conductor only

Terminal Identification Terminals identified in accordance with UL

498 and CSA

#### **Environmental**

Flammability UL 94V-2

Operating Temperature -35°C to 66°C or -30°F to 150°F

## **Accessories**

Wallplates for duplex openings
Solid Right Angle Pigtailed Terminal
Stranded Right Angle Pigtailed Terminal
SNAP2RA

### **Online Resources**

Customer Use Drawing eCatalog Installation Instructions

