Switches, Double Pole, Double Throw 30A, 120-277V AC HBL® Extra Heavy Duty Industrial Switch

Features

• Large brass binding head screws with deep slots

lvory

- Abuse resistant nylon toggle
- Strip gauge for accurate wiring

Ordering Information

Description
Three Position, Two
Circuit, Center Off,
Double Pole, Double
Throw

UPC **Toggle Color** 783585432724

HBL1388I

Catalog Number

Listings

UL Listed CSA Certified Fed. Spec. W-S-896

Specifications

Top Material	Thermoset
Base Material	Thermoset, Green
Toggle Material	Nylon
Contacts	Silver Alloy
Terminal Screws	Brass
Ground Screw	Brass (Green)

Performance

Electrical

Dielectric Voltage	Withstands 1500V AC minimum for 1 minute
Max. Continuous Current	30A
Max. Working Voltage	277V AC
Overload	Minimum 4.8 times rated current for 100 cycles
Temperature Rise	30°C maximum at rated current

Mechanical


Terminal Accommodations #14 AWG min. - #10 AWG max. Solid and stranded copper wire only

Environmental

Flammability **Operating Temperature** UL 94V-2 Max. continuous: 75°C; Min. continuous: -40°C without impact



HUBBELL



Complementary Products

Nylon Wall Plate	NP1I	

Online Resources

Customer Use Drawing
eCatalog
Installation Instructions

