

Wallplate Blank Box Mount 3-Gang

Features

- High-impact, self-extinguishing polycarbonate material
- More rigid; sharp lines and less dimpling
- Smooth satin finish; blends into wall with an optimum finish

| D | Ð | |
|---|---|--|
| | | |
| | | |
| D | D | |

Ordering Information

| | | | | | Catalog | | | | |
|---|---|------------|-----------|--------------|---------|---|---|-----------|-----|
| escription | | Gang | Color | UPC Number | Number | | 0 | O | O |
| Blank box mount | | 3 | lvory | 883778312328 | P33I | | | | |
| smooth satin finish for use with cover | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | O | O | O |
| | | | | | | | 0 | 0 | U |
| Listings | | | | | | | | | |
| cULus Listed | | | | | | - | | 6.50 | |
| | | | | | | | | (1 C - 1) | |
| | | | | | | | | (165.1) | |
| | | | | | | - | | (105.1) | |
| | ns Polycarbor | nate therm | noplastic | | | - | | (105.1) | |
| Material | | ate therm | noplastic | | | - | | (105.1) | |
| Specificatio Material Thickness Orientation | Polycarbor | | noplastic | | | - | | (105.1) | |
| Material Thickness Orientation | Polycarbor .25 (6.4) | | noplastic | | | - | | (105.1) | |
| Material Thickness | Polycarbor .25 (6.4) Orientation | | noplastic | | | - | | | .25 |
| Material Thickness Orientation Mounting | Polycarbor .25 (6.4) Orientation Screw | el | | | | - | | | .25 |



