### **Straight Blade Devices**

15 Amp, 125 Volt, 2-Pole, 3-Wire

## SNAPConnect<sup>®</sup> Extra Heavy Duty Receptacle

# HUBBELL

### **Features**

- Audible SNAP, indicates solid connection
- Reduces installation time
- Tamper-Resistant, LED Indicator
- Assembled in USA

### **Ordering Information**

Description Standard Duplex **Device Color UPC Number** 783585552804 White

Catalog Number SNAP5262WLTRA


### Listings

UL Listed to UL498 File No. E2408 Certified to CSA, C22.2, No. 42 File 507 Fed. Spec. W-C-818 **NEMA® WD-6 Compliant** 

### **Specifications**

Face	Nylon
Base	Nylon
Line Contact	Brass
Ground Contact	Brass

# #6-32 UNC TAPPED HOLE-FOR WALL PLATE SCREW/



### **Performance**

Dielectric Voltage

**Electrical** 

Certified for current interrupting at full rated **Current Interrupting** 

current

Withstands 2,000V minimum

Mechanical

Product Identification Ratings are a permanent part of the device

**Environmental** 

Flammability UL 94V-2

Operating Temperature Maximum continuous 75°C; minimum -40°C

(without impact)

### **Complementary Products**

Wallplate or Weatherproof Cover Opening

### Online Resources

**Customer Sales Drawing** 

eCatalog

Installation Instructions

