### **Straight Blade Devices**

15 Amp, 125 Volt, 2-Pole, 3-Wire

# SNAPConnect® Hospital Grade Receptacle

# HUBBELL

#### **Features**

- · Audible SNAP, indicates solid connection
- Reduces installation time
- Tamper-Resistant
- Assembled in USA

## **Ordering Information**

Description Hospital Grade. Tamper-Resistant **Device Color UPC Number** 783585553368 Brown

**Catalog Number** SNAP8200TRA




## Listings

UL Listed to UL498 File No. E2499 Certified to CSA, C22.2, No. 42 File 598 Fed. Spec. W-C-909 NEMA® WD-6 Compliant

## **Specifications**

Face	Nylon
Base	Nylon
Line Contact	Brass
Ground Contact	Brass



#### **Performance**

**Electrical** 

**Current Interrupting** Certified for current interrupting at full rated

current

Withstands 2,000V minimum Dielectric Voltage

Mechanical

Product Identification Ratings are a permanent part of the device

**Environmental** 

UL 94V-2 Flammability

Maximum continuous 75°C; minimum -40°C **Operating Temperature** 

(without impact)

# **Complementary Products**

Wallplate or Weatherproof Cover Opening

#### **Online Resources**

**Customer Sales Drawing** eCatalog

Installation Instructions

