

# WEEB-ECR, WEEB Top Clamp Washer, 2.16 IN L, 1.17 IN W, 0.33 IN hole size, Rigid

By WILEY Catalog # WEEB-ECR

304 Stainless Steel Electrical Equipment Bond Washer; 2.16" Length; 1.17" Width; 0.28" Height; 0.33" Hole Size; Rigid.



#### **Features**

- Made from corrosion resistant 304 stainless steel for outstanding durability and performance
- Eliminates the need for surface preparation and oxide inhibitor.
- Detailed manual specifying proper hardware, torque, and mounting information is available upon request
- UL467 Recognized for grounding and bonding equipment
- Custom grounding and bonding solutions available upon request

#### General

Application WEEB washers offer a simple,

low cost method to bond any non-conductive coated surfaces together reducing time, labor costs and the amount of copper wiring.

WEEB's patented teeth pierce through most non-conductive coatings and embed into the underlying metal creating a bonding connection between the mounting surface and coated metal component that it

is installed on or between.

Catalog Number WEEB-ECR

Item Type 4D

 Material
 304 Stainless Steel

 UPC
 781810537497

 UPC 12 Digit
 7818105374977

### Dimensions

Dimension - Thread Size -

## **Certifications And Compliance**

 $\begin{array}{lll} \text{Certification - CSA Approved} & \text{N} \\ \text{Certification - ETL} & \text{Y} \\ \text{Certification - UL Recognized} & \text{Y} \\ \text{Certification - cULus} & \text{N} \\ \end{array}$ 

Certified Listed UL2703 Recognized Industry Standard(s) UL2703 Recognized

Standards - RoHS Compliance

Status

UL Listed Yes

## Logistics

Carton Quantity 6000

# **Product Assets**

Brochures - WEEB Washer Guide and WEEB Washer Theory Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Catalogs - BURNDY Master Catalog - Section E4 - Wiley

Grounding

Certifications - UL Standard for Safety for Grounding & Bonding

Equipment, UL 467, CSA C22.2 No. 41-13 Customer Notices - Prop 65 Notice Sales Drawings - 50001976



©2024 Hubbell Incorporated. All rights reserved WLY-WEEBECR-SPEC-EN | REV 6/2024